

APPLICATION

Use in domestic premises and offices, for ordinary duty applications and household appliances, including in damp premises; or fixed installation in dry or damp premises on walls, boards or trays, in channels or embedded in plaster.

ELECTRICAL CHARACTERISTICS

Conductor style: Flexible

Conductor material: Copper

Feature: Flat

Insulation/Sheath: PVC

Temperature: : 70°C maximum

Operating Temperature Rated : -20°C ~ +70°C



SPECIFICATION

Model(mm²)	Description	Outer Diameter	Rated Power	Voltage	Weight
2 x 0.5	2*16/0.2mm	3.3x5.4mm	800W	300/500V	3.0kgs
2 x 0.75	2*24/0.2mm	3.7x5.7mm	1100W	300/500V	3.8kgs
2 x 1.0	2*32/0.2mm	4.2x6.3mm	2000W	300/500V	4.7kgs
2 x 1.5	2*48/0.2mm	4.4x7.2mm	2900W	300/500V	6.6kgs
2 x 2.5	2*80/0.2mm	5.0x9.3mm	4800W	300/500V	9.1kgs
2 x 4	2*80/0.25mm	5.5x12mm	7200W	300/500V	13kgs
2 x 1 (Solid)	2*1/1.12mm	7.3mm	2100W	300/500V	4.6kgs
2 x 1.5 (Solid)	2*1/1.38mm	7.5mm	3500W	300/500V	6.5kgs
2 x 2.5 (Solid)	2*1/1.78mm	7.9mm	5000W	300/500V	9kgs
2 x 4 (Solid)	2*1/2.26mm	9.4mm	7800W	300/500V	11.6kgs