

Portable Thermal Printer HCC-T3P-B

Feature

- Mini size, Light weight, Durable performance
- 1500mAH, 7.4V rechargeable Li-ion battery, quick charge
- Continuously work for 6 hours
- 80mm/s high printing speed
- Support various languages, easy to use
- Standard interface: USB(Virtual Serial), Bluetooth, WIFI (Apple and Android)
- Support Dots Printing With different densities
- Support raster Bitmap Print
- Support 1D and 2D QR CODE Printing
- Support OEM\ODM
- Support Windows(Win10/WIN7/WIN8/Vista/XP/2000)
- Ubuntu 12.04 32/64, Ubuntu 14.04 32/64 drivers.
- Free SDK templates For Linux(C++),Windows,Android, IOS

Specification

Print	Printing Method	Thermal Line
	Printing Speed	60mm/s(average), 80mm/s(max)
	Resolution	8 dots/mm, 384 dots/line
	Effective Printing Width	72mm
Communication	Wired	Standard:Mini-USB Port, Optional:Serial Port(PS/2)
	Wireless	Bluetooth+USB / USB+WIFI
Character	Character Set	ASCII9*17,12*24, GB2312-80(Chinese)
	Print Font	ANK:(8x16,9x17,9x24,12x24), GBK: 16x16,24x24
	Language(Code Page)	Support Simplified & Traditional Chinese, English and other 45 kinds of International Character Sets
Paper Spec	Paper Type	Thermal paper
	Paper Width	80±0.5mm or 76±0.5mm
	Paper Roll Diameter	Max:40mm
Soft wares	Drivers	Windows(win10/ win8/win7/vista/XP/2000); Ubuntu 12.04 32/64untu 12.04 32/64 Ubuntu 14.04 32/64
	App	Printer setting tools
Barcode	1D	UPC-A, UPC-E, EAN-8,EAN13, CODE39, ITF, CODEBAR, CODE128 Etc..
	2D	QR Code
Indicators LED		Power(red), Battery Charging(Green), Bluetooth and out of paper(Blue)

Paper tore		Manual
Detection Sensor		Out of Paper
Battery		Rechargeable Li-ion Battery, 7.4V, 1500mAh
Charger Power Supply (Adapter)		Input:100-240VAC/0.5A, 50/60Hz; Out Put: 5Vdc/2A
Environment	Operating Temp	5°C ~ 50°C
	Operating Humidity	10% ~ 80%
	Storage Temp	-20°C ~ 60°C
	Storage Humidity	10% ~ 90%
Interface		USB+Bluetooth
Package info		One set size: 210*125*65mm One set Weight: 0.6kg
Standard Accessory		1* User Manual, 1* CD Driver, 1* Power Adapter 1*USB Data Cable 1*Test Paper Rolls 1*battery

Picture



Shenzhen HCC Technology Co., Ltd.

 Address: Rm. 201, 2/F, Bldg. 8, Changyuan New Material Port, No. 2 Gaoxin C. 1st Ave., Yuehai St., Nanshan Dist., Shenzhen, P.R.China
 Post Code:518057 Tel:86-755-86655162 Fax:86-755-8606-9640 Web:www.szhcct.com