





PCB LAYOUT



KEY SPECIFICATION:

- 1.RATING:DC 50V 0.3A
- 2.FNCATION:2P3T
- 3.CONTACT RESISTANCE:100m OHM MAX
- 4.INSULATION RESISTANCE:100M OHM MIN
- 5.DIELECTRONIC STRENGTH:AC 500V FOR 1MIN
- 6.OPERATING FORCE:250gf±100gf
- 7.OPERATING LIFE:10,000CYCLES
- 8.OPERATING TEMPERATURE:-20°C~+70°C

8					TOLERANCE UNLESS SPECIFIED				
7	STEEL BALL	STAINLESS STEEL	1	NATURAL					
6	CONTACT	BRONZE STRIP	2	Ag PLATED	WITHIN 1.5: ±0.1mm OVER 1.5: ±0.2mm ANGLES: ±2°				
5	SPRING	STELL WIRE	1	NATURAL		ISSUE	DATE	DESCRIPTIONS	APPD.
4	TERMINAL	BRASS STRIP	8	Ag PLATED		TITLE:SLIDE SWITCH			
3	BASE	PHENOL IC RESIN	1	NATURE		UNIT:mm		DRWG. NO.:	
2	SHELL	SPCC STRIP	1	Ni PLATED		MODEL NO: SS-23H06G()		SCALE:4:1	DWN
1	KNOB	POM	1	BLACK					CHK'D
NO.	DESCRIPTION	MATERIAL	QTY	PLATING		DONGGUAN JINBAOLI ELECTRONICS CO.,LTD			APPD.