

Specification

Model Number	VTS02-G-H-DL
DSP	AK KM01N-C
Operating system	Android, IOS
APP:	V380 PRO
Sensor:	1/2.9" Progressive Scan CMOS (GC3003*2)
Video compressed format:	H.265
Resolution:	2304*2592P
4G Network :	4G-BAND1/3/5/8/38/39/40/41
Detection method:	PIR + Radar dual induction detection
Detection distance:	0~12M
Detection angle:	120°
Alarm method:	Double induction confirmation and push alarm information mobilephone
Pan-tilt:	Horizontal: 355 °, vertical: 90°
Rotate speed	Horizontal 55°/seconds, vertical 40°/seconds
IR Leds	8pcs Dual Core LED
Full color night vision:	minimum illumination 0.00001LUX
Infrared Led:	Infrared LED distance: 30M, effective distance :10M
White Led:	White LED distance: 30M, effective distance :10M
Built-in speaker:	3W
Built-in microphone:	Audio pick-up eara about 20M
Lens:	fixed-focus 2.8mm and 8mm+3.6mm
Angle:	80°
Cloud storage:	Cloud Storage (Alarm video)
Local storage:	TF card (Max 128G)
power supply mode :	solar panel + 3.7V 18650 battery
Solar panel power:	8W
Battery capacity	Built-in 8000mah battery
Operating power	daytime: 350-400ma, Night time:500-550ma
Standby power	5 mA
work environment:	IP66 Waterproof, can use indoor and outdoor
Working	-30°~+50°
Working humidity:	0%~80%RH

Color box	26.6*19.6*14.5cm
Carton size	61*56*31cm
Carton quantity	12pcs.