

| Description                     | Unit           |      | Parameter value |
|---------------------------------|----------------|------|-----------------|
| Rated operating load            | kg             |      | 5000            |
| Bucket capacity                 | m <sup>3</sup> |      | 2.5~4.5         |
| Machine weight                  | kg             |      | 17500±300       |
| Dump clearance at maximum lift  | mm             |      | 3100~3780       |
| Reach at maximum lift           | mm             |      | 1100~1220       |
| Wheel base                      | mm             |      | 3300            |
| Tread                           | mm             |      | 2250            |
| Max.breakout force              | kN             |      | 175±5           |
| Max.horse power                 | kN             |      | 160±5           |
| Hydraulic cycle time-raise      | s              |      | ≤6              |
| Total hydraulic cycle time      | s              |      | ≤10.5           |
| Min. turning radius over tyres  | mm             |      | 5925±50         |
| Articulation angle              | °              |      | 38              |
| Gradeability                    | °              |      | 30              |
| Tyre size                       |                |      | 23.5-25-16PR    |
| Overall machine dimension L×W×H | mm             |      | 8225×3016×3515  |
| Model                           |                |      | WD10G220E21     |
| Rated Power                     | kW             |      | 162             |
| Travel Speed                    | I -gear(F/R)   | km/h | 13/17           |
|                                 | II -gear(F)    | km/h | 41              |