

JS-Series Solid State Disk								
Name		PATA	SATA	CF	DOM	UDOM	SATA+USB	PATA+USB
Model Number		SCPAF2***GB-*	JSBSAF2***GD- *I	JSGCFFI***GB- *I	JSCPAFD***GB-*I	JSCPAFD***GB-*I	JSBSUF2***GD-*I	JSCPAF2***GA-*I
Physical characteristics	Interface	PATA	SATA	CFA2.0	IDE	USB	SATA+USB	PATA+USB
	Capacity	4G~128G	1G~128G	1G~16G	1G~4G	1G~8G	1G~128G	1G~128G
	Size(mm)	100.2 ×70.0×9.5	100.2 ×70.0×9.5	42.8 ×36.4×3.3	47.8×32.6×7.5(hole) /10.0 (stitch)	52.0×31.0×6.40	100.×70.0×9.5	100.2×70.0×9.5
	Memory	SLC NAND FLASH						
	Enclosure	Black spray-paint&conventional Al		Standard	None	None	Black spray-paint &conventional Al	
Performance parameters	ECC error correction	Corrected 8-bit random errors as per 512 bits						
	Continous read speed	>50MB/s	140MB/s	29MB/s	36MB/s	20MB/s	140MB/s	27MB/s
	Continous write speed	>50MB/s	80MB/s	19MB/s	22MB/s	10MB/s	80MB/s	20MB/s
	I/O operation as per second	5000IOPS						
Environmental index	Operating temperature	-40℃ — +85℃						
	Storage Temperature	-60℃ — +95℃						
	Relative humidity	5%~95%, Noncondensable						
Reliability	MTBF	100 million hours						
	Data integrity	10 years						
	Write endurance	105 years @100GB/Day Erase/Write						
	Read endurance	Infinite						
Professional high quality services	PCB three-prevention technologies	Optional (Three-prevention technologies: water-proof;anticorrosive, dust-proof and water-resistant)						
	Warranty period	One year						
	Lead time	One Month						
	Customized service	None						
	Marketing	Industrial reinforcing machine, industrial instruments, IPC, POS machine, switch, lottery machine						