


***为防止LCD产生图像残留，在使用常黑面板时不要长时间显示固定图案。如果LCD需要显示固定图案，建议时间少于 2 分钟或者更短的时间内刷新显示内容一次或多次。
***In order to prevent the LCD from producing image retention, do not display a fixed pattern for a long time when using a normally black panel. If the LCD needs to display a fixed pattern, it is recommended to refresh the display one or more times in less than 2 minutes or less.
强烈建议使用黑色图像或移动图像作为屏幕保护程序。It is strongly recommended to use a black image or moving image as a screen saver.

字体：黑体
bold (typeface)

[illegible]

观看方向/角度 Viewing Direction	U85/D85/L85/R85(Typ.)	TFT 储存温度 TFT Storage Temp	-20 °C ~ +70 °C
接口 Interface	4-wire 8-bit data serial interface	TFT 储存温度 TFT Storage Temp	-30 °C ~ +80 °C
工作电压 Operating Voltage	VCI=+3.2±0.2V	背光驱动条件 Backlight conditions	Vf= 3.0 ~ 3.4V, If=40mA
驱动芯片 Driver IC	GC9A01<TFT>	液晶模组亮度 LCM Brightness	500 cd/m ² (Typ)/恒流

The logo for HOTIMI is displayed, featuring a stylized 'H' in green and blue, followed by the text 'HOTIMI' in a grey, sans-serif font.

产品型号 Product model				TFT-H013A6QQIGC5N10	
比例 Scale		1:1		设计制图 Design	
		Liu.YL		日期 Date	
				2024-12-1	
版本 Ver		V2-0		单位 Unit	
		MM		公差 Tol.	
				±0.3	