

Mini Mobile Thermal Printer HCC-T12

Feature

1. Small size, ultra-light; support a variety of alarm;
2. Support playing edge charging, no battery printing, car charging;
3. Large battery capacity;
4. Full-featured, print clear, easy to carry.

Specification

Performance	Printing Method	Thermal Line
	Printing Speed	62mm/s
	Resolution	8 dots/mm; 384 dots/line
	Effective Printing Width	48mm
	Paper Width	57.5±0.5mm
Printing support	Chinese	GB three characters: 16 × 16 dot matrix, 24× 24 dot matrix
	Western	ASCII: 8x16 dot matrix, 9 × 24 dot matrix, 12× 24 dot matrix
	Custom characters	support
	Graphical printing	Support different density dot graph and download graphic print
	Barcode	1D: UPC-A; UPC-E; EAN-13; EAN-8; CODE39; 2D: PDF417; QRCODE; DATAMATRIX
Paper Specification	Paper Type	General Thermal paper
	Paper Width	57.5±0.5mm
	Paper Thickness	0.06~0.08mm
	Paper Supply Method	Drop-in easy paper loading
	Paper Cutting Method	Manual tearing
	Paper Roll Diameter	40mm (Max)
Interface	USB /RS-232/ Bluetooth	
Support function	out of paper alarm, overheating protection, black mark positioning,	

	automatic sleep, the battery power alarm
power supply	battery: 1500mAh
	charger: External power supply printing is not supported
Physical properties	physical dimension: 106.5mmx78mmx47mm (LxWxH)
	weight: 190g (No paper rolls)
Environment	Operating Temperature/ Humidity: 0~50℃/10~80%
	Storage Temperature/ Humidity: /10~80%/10~90%
Life/Reliability	Printer head life: 50km
SDK	Windows CE; Windows Mobile 5.0/6.0; Symbian; Blackberry and Android;Support IOS, and conformance with MFI certificate

Model:

T12	T12BT	Android
	T12I	Android and iOS

Picture
