

VSDB 4390 DEVICE PARAMETERS

Product Name	VSDB4390 Single Layer Banana Sieve	Screening area(m ²)	38.7
Applicable materials	Dry classification of granite, limestone and other products, de-powdering of limestone.	Amplitude(mm)	9-10
Screening method	Wet screening dewatering	Vibration frequency (rpm)	950-1050
Feed size	0-10mm, sieved 4mm fine sand	Inclination	30°-13°
Processing capacity (t/h)	1000	Motor power	90KW/unit
Recovery volume (t/h)	300-400	Appearance (length*width*height)	9.5m*5.2m*5.5m
Total weight	Parameter weight 26.7 tons total weight 39.2 tons		

VSDB SERIES SPECIFICATIONS AND PARAMETERS

Model	Screening area (EACH FLOOR M ²)	Processing volume (T/H)	Vibration weight (KG)	Drive unit	Exciter	Total weight (KG)	Length*Width*Height
1848	8.64	220-500	5700	22KW	SW317S*2	6260	5675*2590*2880
2161	12.81	300-900	7150	22KW	SW317S*2	7850	6845*2895*2990
2496	23.04	420-1000	14200	37KW	DF504S*2	15400	9900*3250*5180
3085	25.5	550-1300	13900	37W	SW322V	15100	9182*3860*3820
3685	30.6	650-1650	19800	55KW	SW326V	21100	9100*4600*4292
4390	38.5	800-2000	28000	90KW	SW326V	43600	10302*5200*5896