

Product Parameters Table:

Parameter	Details
Product Name	Distal Lateral Fibula Locking Plate II (L/R)
Material	Medical-grade titanium
Surface Treatment	Polished and anodized for corrosion resistance and minimal soft tissue irritation
Plate Type	Locking plate for distal lateral fibula
Available Versions	Left and right configurations
Holes Configuration	3, 4, 5, 6, 7, 9, 11 holes
Length (mm) (2.4/2.7)	71 mm, 84 mm, 97 mm, 110 mm, 123 mm, 149 mm, 175 mm
Length (mm) (3.5)	71 mm, 84 mm, 97 mm, 110 mm, 123 mm, 149 mm, 175 mm
Screw Compatibility	HA 3.5 mm screws, Locking screws 2.7 mm and 3.5 mm
Indications	Distal fibula fractures, osteotomies, deformity correction surgeries
Contraindications	Active infection, poor bone quality, titanium allergies
Sterilization	Supplied unsterile, requires sterilization before use
Fixation Type	Rigid fixation using locking screws
Intended Surgical Approach	Open reduction internal fixation (ORIF) for distal fibula fractures and osteotomies
Packaging	Non-sterile packaging, requires sterilization before use
CE Certification	Certified for international use (CE compliant)
Shelf Life	5 years when stored under appropriate conditions
Radiolucency	Radiolucent for use with imaging modalities like X-ray and CT
Customization	Available in different lengths and configurations for patient-specific needs
Usage Environment	Designed for sterile operating room conditions