

Portable Bluetooth Printer

PRINT PARAMETERS	
Print Method	Straight Thermal Print
Print Resolution	203×203DPI
Print Speed	50-80mm /sec
Power Available	150-280M
Standby Time	100H
Sensors	Temperature of print head and Paper out
Battery Capacity	2000MAH
Charge Method	12V1A
Charge Time	2-4H
Paper Type	Thermal paper roll
Paper Diameter	Maximum 50mm
Paper Spec.	80mm±0.5mm(width) 0.05-0.10mm(Thickness)
Printer Width	72±0.5mm
Character Set	Chinese-Simplified,ASCLL(12*12), ASCLL(9*17)
Size(L*W*H)	130*100*155mm
Color	Grey
Weight	1.5kg
Operating Temperature	10degrees to 50 degrees(32 Fahrenheit to113 Fahrenheit)
Storage Temperature	-20degrees to 70degrees(-40 Fahrenheit to140 Fahrenheit)
Operating Humidity	20% to 50%
Storage Humidity	5% to 95%
Printer Control	Compatibility with ESC/POS
Language Available	Chinese, English, Japanese
Picture Available	Andriod support Dot-matrix Printing; IOS not support picture printing
Curve	Available
Barcode Available	EAN-13, EAN8, CODE39, CODE93, CODE128, ITF, CODEBAR, UPC-A, UPC-E
2D Barcode	QR CODE, PDF417
Windows	USB & 203 Driver
Linux	USB cable connection
INSPECTION	
Lacking of Paper	Photoelectric Detection
Black Marks	Right-Black marks Available
Shortage of Power	Lights Flashing
Package	
Package size	220mm*120mm*75mm