



AMC-G200T speaker tracking camera helps to achieve intelligent meeting experience, implemented with both audio positioning and intelligent video analysis technology, it can automatically switch between close-up image to frame speakers and full view image to frame the whole room, it frees of camera operation during a meeting and enables meeting attendees to focus more on discussion.

Features

- ※ 1/2.8" Exmor CMOS, 2MP
- ※ 12X optical zoom up to 72.5° Fov
- ※ Simultaneously output 3G-SDI, HDMI, Ethernet, Up to 1080p60 resolution
- ※ Support H.264/H.265 video compression
- ※ Implemented with both 3D voice positioning technology, body detection and recognition algorithm, it can precisely frame the speakers
- ※ Automatically switch between close-up image for speakers and wide angle image for meeting participants.

Technical Data

HD Camera	
Image Sensor	1/2.8" Exmor CMOS, 2.14MP
Signal Format(SDI)	1080p/60, 1080p/50, 1080p/30, 1080p/25, 1080i/60, 1080i/50, 720p/60, 720p/50
Focal	f=3.9mm-46.8mm
Iris	F1.6 - F2.8
Optical Zoom	12x
Digital Zoom	12x
Field of View	72.5° - 6.3°
Focus	Auto, Manual, PTZ Push, One Push
Min.illumination	0.5Lux(Color), 0.1Lux(B/W)
Shutter Speed	1/25 - 10.000s
AGC	Auto/Manual
White Balance	Auto, Indoor, Outdoor, One Push, Manual, Auto Track
AE Control	Auto, Manual, Shutter Priority, Iris Priority
S/N	Above 50dB
DNR	2D/3D
BLC	Support

PTZ

Pan/Tilt Angle Range	Pan: -90° - +90° ; Tilt: -30° - +90°
Pan/Tilt Speed	Pan: 0.1° - +120°/s ; Tilt: 0.1° - +80°/s
Preset Number	256
OSD	Yes
Image Flip	Yes

Network

Max,Image Size	1920x1080 @ 60fps
Video Compression	H.264, H.265
Audio Compression	AAC
Protocol	HTTP,RTSP,RTMP,TCP,UDP,ONVIF
Dual Stream	Support

Interface

Video Output	1 x HDMI Interface, 1 x 3G-SDI interface
Audio Input	1 x Line in
Audio Output	1 x Line out
Network Interface	1 x 10M/100M
USB interface	1 x USB 2.0
Control Interface	1 x RS232

General

Control Protocol	VISCA / PELCO-P / PELCO-D
Address	0-63
Power Supply	DC12V
Power Consumption	Below 50W
Working Temp	0°C - +40°C
Storage Temp	- 20°C - +60°C
Dimension	500mm x 163mm x 145mm
Weight	3KG

※※※ Product specification are subject to change without notice ※※※