

Haoliyuan (Shenzhen) Electronic Co., Ltd

E-mail:julie@haoliyuan.net

Mobile:+86-15220117341

Skype ID:julie_4139

Know about the LCD Displays Temperature & Humidity Sensor

This is a smart LCD Displays temperature and humidity sensor, adopts super low power Zigbee networking technology with 2*AAA battery, makes a longer battery life, it can monitor real time temperature and humidity at home and report them to app and show on LCD displays also. Suitable to be used for residential villas, factories, shopping malls, warehouses, office buildings, banks, computer room and other places environment monitoring.



LCD Displays	Blinking	The device enters network configuration mode
	ON	The device is under standby status
Button	Reset or enter configuration mode	Press and hold the button for 5 seconds until the LCD Displays blinks, the device will enter configuration mode
	Trigger to report current status	When the device is under standby status, press the button one time and the device will report its current status to gateway.

Haoliyuan (Shenzhen) Electronic Co., Ltd

E-mail:julie@haoliyuan.net

Mobile:+86-15220117341

Skype ID:julie_4139

Technical parameters

App/Platform	Tuya
OS support	Android/IOS
Transmission Protocol	Zigbee, IEEE802.15.4
Work Frequency	2.400-2.483GHz
Output Power(Max)	+10dBm
Power support	2*AAA Lithium Battery
Zigbee Wireless distance	Max 90 meters(Empty area)
Measure Temperature Range	-20°C~+60°C, ±2°C
Measure Humidity Range	0~100RH, ±5%RH
Operating Temperature	-10°C~+50°C
Operating Humidity	Maximum 95%RH
Materials	ABS
Dimension(LxWxH)	75x17x45mm
LCD displays Temperature, Humidity and internet time	
3 type methods to install: Stand directly - Magnetic - Sticker. It can be stand directly at table/any place without any cradle. Secondly, built-in magnet can hanging on anywhere with iron.	