

Daisy Xiang Sales Manager

FIRST INDUSTRIAL DEVELOPMENT CO.,LIMITED

tel:0086 577 6256 8230 fax: 0086 577 6256 8230

mobile: 86 158 2544 3655(whatsapp,wechat)/ 86 133 8858 7626

web: www.firsth2o.com

email: daisy@firsth2o.com,info@firsth2o.com

skype:Daisyxiang123

Stainless Steel Drinking Water Fountains

	Model:		UCWC-1(Cold only)		UCWC-2 (Cold only)	
	Rated Voltage:		220-240V/ 50H/110-120V /60Hz/127V/60Hz			
	Rated Power:	Heating:	N/A		N/A	
		Cooling:	150W		120W	
	Compressor Type:		Hermetic, with overload protector, R134a			
	Cold Water Tank Capacity:		2.0L		2.0L	
	Cooling Capacity:		12L/H at <10°C against ambient temperature 25°C		8L/H at <10°C against ambient temperature 25°C	
	Filter System:		N/A			
	N.W		14.5kg (31.9lb)		13.5kg(29.7lb)	
	G.W		15.5kg(34.1lb)		14.5kg(31.9lb)	
	Machine Diemension:		375*260*305(mm)		375*260*305(mm)	
			14.8(D) x10.3"(W) x 12"(H)		14.8(D) x10.3"(W) x 12"(H)	
	Packaging Diemension:		420*320*390mm		420*320*390mm	
			16.5"(D) x12.6" (W) x 15.4" (H)		16.5"(D) x12.6" (W) x 15.4" (H)	
	MOQ:		1*20FCL		1*20FCL	
	Required Water Pressure:		0.07-0.5Mpa			
	Required Water Source:		City Water			
	Loading Quantity:		1*20FCL	588 units	180 units	

Fan Cooling UCWC-1

Natural Cooling UCWC-2

- Under Counter Chiller: under-sink cold water dispenser
- Faucet not included with unit.
- Chilled and Ambient (room temperature)
- Suitable for 4-8 users
- Suitable for home or office use
- Compressor cooling with ventilated condenser
- Stainless steel cold tank: 2.0 liters
- Included push-fittings for ¼” piping

Parts required for installation:

- ¼” Pressure Reducing Valve
- ¼” Saddle Clamp
- ¼” LLDPE tubing per meter (length as required)
- Single Faucet – Chilled water only
- Dual Faucet – Chilled and Ambient water

Hot Item!!