

10 inch LCD 4CH Wireless NVR KIT KIT-1042

Features :

- 4 pcs Wireless Metal IR Bullet Camera;
- 5:36pcs IR LED,3.6mm Fix Lens;
- 10 inch 4CH Wireless 2MP/5MP NVR;
- 4pcs DC 12V 1A Power Adapter;
- 1pcs DC 12V 2A Power Adapter;
- Support VGA 1080P, HDMI 1080P output;
- Mini 1U Case,1 SATA(Up to 8TB);
- H.265+/H.265/H.264 image decoding ;
- 1*10/100Mbps Ethernet port, RJ45 port ;
- Automatic networking,automatic add IPC;
- Supports the Onvif protocol and can connect to third-party devices;
- Support GB28181 protocol to access third-party platforms (optional);
- Support cloud service, network penetration and alarm information push function;
- Support remote access, with its own domain name service function (ARSP) ;
- Support TCP/IP,IPv4,DHCP,NTP,RTSP,Onvif,P2P,SMTP, GB28181 Protocol, etc.;
- Support mobile phone monitoring (iOS, Android);
- Support multiple browser access (IE, Chrome, Firefox,Safari);
- Support more than 20 languages and break the boundaries of national borders;
- Perfect protection circuit, unique triple watchdog function;

Package :



Parameters :

Item	KIT-FHM/THT/TES/THS/THF-1042
Processor	ANKAI/HiSilicon
System	Embedded LINUX operating system
Encode	4*720P/4*960P/4*1080P/4*5M
Playback	1CH Playback
Preview	1/2/4
Codec	H.265+/H.265/H.264
Compression	G.711A
Wireless	2.4G
APP	IP-Pro
CMS	EseeCloud For PC
Record mode	Manual>Alarm>Motion detection>Timing
Storage mode	HDD Storage, Network Storage
Backup	Network, USB, SATA
HDMI output	1*HDMI (MAX:1080P)
VGA output	1*VGA (MAX:1080P)
Ethernet port	1*10/100Mbps Ethernet port, RJ45 port
Protocol	UPnP(play&plug)/SMTP(email service)/PPPoE(dial-up)/DHCP(Automatically obtain an IP address),etc
Audio I/O	Support Microphone and Speaker on IPC
Alarm I/O	0/0
USB Port	2*USB 2.0 port
HDD	1*SATA interface (Up to 8TB)
Temperature	-10 °C - + 55 °C
Humidity	10% -90% RH
Power supply	DC 12V
Consumption	<5W (Without HDD)
Weight	Around 2.5KG
Dimension	280mm (W) ×230mm (V) ×55mm (H)