



SHENZHEN RISE ELECTRONIC CO., LTD.

Website: <http://www.ideacamera.com> Email: cctv@ideacamera.com

Global Sources Homepage Address: <http://www.globalsources.com/ideacamera.co>

32CH 2SATA H.264 HD Professional NVR, VSS Mobile App, ONVIF 2.6, Max 32ch Playback, Support Max 6MP IPC.



Key Features:

Model: NVR-3132-CS

32CH Face Detection work with VSS IP Camera (HISI)

H.264 Format, Support ONVIF 2.6 protocol

IP input: 32ch@720/960/1080P / 3.0/4.0MP/5.0MP/6.0MP@30fps

Bandwidth: 200Mbps

Support 2SATA HDD (10TB)

Support Max 1~32ch real-time playback

Audio: 32ch in by RJ45, 1ch in by RCA, 1ch out by RCA

Support Multi-Protocols/P2P/Cloud Storage (google drive/drop box)

Built-in free DDNS/UPNP/3G Dongle supported/Digital zoom/Mobile phone surveillance

1 x VGA port, 1 x RJ45 ports; 1 x HDMI ports; 2 USB2.0 ports, 1 x RS485 port

Remote controlling, Mouse controlling

Mobile phone APP: VSS Mobile (support IOS/Android system)

Computer client controlling (IMS300 platform)

Standard configuration power (DC 12V 3.3A)

Offer services:

Offer 2-years product warranties.

Logistics convenient.

OEM/ODM.

CCC/CE/FCC Certified.

Strict product quality control.



SHENZHEN RISE ELECTRONIC CO., LTD.

Website: <http://www.ideacamera.com> Email: cctv@ideacamera.com

Global Sources Homepage Address: <http://www.globalsources.com/ideacamera.co>

Lower price.

6-8 working day per order.

Applications:

This is the best product of safety field. It and CCTV camera、cable、power supply、display、etc. Constitute a complete security system. Tts application is more extensive. Such as homes、factories、highways、office building、garden、community, or a large public places, etc.

Parameters:

Model		NVR-3108-CS	NVR-3108-P8/CS	NVR-3116-CS	NVR-3116-P8/CS	NVR-3132-CS	NVR-3132-P8/CS
OS		Embedded Linux					
Video&Audio input	Bidirectional Talk	1CH, BNC(Line in, 2Vpp, 1Kohms)					
	Incoming bandwidth	96Mbps		128Mbps		200Mbps	
	Outgoing bandwidth	64Mbps		64Mbps		160Mbps	
	IPC Input	8CH		16CH		32CH	
Video&Audio output	CVBS	1CH, BNC(1.0Vp-p, 75ohms)					
	VGA	1CH, 1920×1080, 1280×1024, 1280×720, 1024×768					
	HDMI	Standard 1.3a					
		1920×1080, 1280×1024, 1280×720, 1024×768					
Audio Output	1CH, BNC(Line out, 2Vp-p, 300ohms)						
Video&Audio encoding	Audio Compression	G. 711A					
	Audio Bit Rate	64Kbps					
Video&Audio decoding	IP channel Resolution	Main stream:Up to 2560x1920 Auxiliary stream:D1					
	Video decoding	MPEG-4/H. 264(Up to High Profile@Level4.2)					
	Audio decoding	G. 711A/G. 726					
	Synchronous Playback	Up to 8CH		Up to 16CH		Up to 16CH	
	Decoding Ability	8CH 720P@30FPS or 6CH 1080P@30FPS		13CH 720P@30FPS or 6CH 1080P@30FPS			
Intelligent Analysis		1CH Face detection or 2CH Perimeter detection				N/A	
		Up to 1080P					
Other Function	Bidirectional Talk	Two-way voice intercom function					
	Motion Detection	Zones: 396(22*18),Sensitivity: 1~6 (level 6 is highest)					
	Picture Capture	Support JPEG Capture					
HDD Interface	SATA	2 SATA Interfaces					
	Max Capacity	Unlimited					
POE Interface	POE Interface	N/A	8CH	N/A	8CH	N/A	8CH
			IEEE 802.3af /Switch		IEEE 802.3af /Switch		IEEE 802.3af /Switch



SHENZHEN RISE ELECTRONIC CO., LTD.

Website: <http://www.ideacamera.com> Email: cctv@ideacamera.com

Global Sources Homepage Address: <http://www.globalsources.com/ideacamera.co>

			RJ-45 10/100 Mbps self- adaptive Ethernet interface		RJ-45 10/100 Mbps self- adaptive Ethernet interface		RJ-45 10/100 Mbps self- adaptive Ethernet interface
	Power	N/A	≤90W	N/A	≤90W	N/A	≤90W
External Interface	Network Interface	1 RJ45 10M/100M/1000M self-adaptive Ethernet interface					
	USB	2 USB2.0 Interfaces					
	Alarm Input	8CH					
		Open/Closed Relay					
	Alarm Output	3CH					
		NO/NC					
	RS-485	1 RS-485 interface					
Structure	Dimensions	405*335*120mm					
	Front Panel	LED					
	Size	1U, 360*262*48mm					
	Weight	2. 3Kg(without HDD)	3Kg(without HDD)	2. 3Kg(without HDD)	3Kg(without HDD)	2. 3Kg(without HDD)	3Kg(without HDD)
	Installation	Desktop Installation					
General	Power Supply	DC +12V 3. 3A		DC +12V 3. 3A		DC +12V 3. 3A	
		N/A	DC +48V 1. 875A (POE)	N/A	DC +48V 1. 875A (POE)	N/A	DC +48V 1. 875A (POE)
	Working Temperature	-10℃--+55℃					
	Working Humidity	10%--90%					
	Consumption	10W(without HDD, without POE)		10W(without HDD, without POE)		10W(without HDD, without POE)	