



Shenzhen Yushang Electronics Co., Ltd

Peter Email: peter@yspmd.com Mob: +86 13926593072 www.yspmd.com
Add: F4-6, Block A2, Tianrui Industrial Zone, Fuhai Street, Baoan District, Shenzhen, CN

55inch Floor Standing Double Sided Digital Signage Kiosk With Android OS CD-55EG8



Display Data	Size	55 inch (1387mm)
	Resolution	3480*2160
	Viewing Angle	L/R178, U/D178
	Brightness	420CD/M2
	Display ratio	16:9
	Frequency	60Hz
	Type	TFT-LCD+LED backlight
Hardware (Taking Android as basic, Windows with I3/I5/I7 CPU optional)	CPU	Quad core Cortex-A17 RK 3288 processor 1.8GHz
	RAM	2GB DDRIII
	Storage	16GB
	OS	Android5.0 above
	Internet	WiFi 802.11 b/g/n
	I/O ports	USB2.0*2, USB3.0*2
Main control board interface	Power	1 external socket
	HDMI Output	1, support HDMI2.0@60Hz 4K*2K screen
	Network	1 *RJ45 10M / 100M Adaptive Ethernet port
	HDMI Input	1
	Earphone/Mic	1, External headphone audio output socket (GB: GND, MIC, R, L)
	WiFi	1*WIFI, Support 2.4G/5G WIFI, Support Wi-Fi 802.11b/g/n
	3G/4G (optional)	Scalable 1 channel 3G (WCDMA, EVDO, CDMA, GSM) / 4G (LTE-TDD / LTE-FDD / TD-SCDMA / EDGE / GPRS / GSM) signal
	SD Card	Maximum expansion to 64GB TF card
	USB2.0	2, USB HOST
Shell	Material	Tempered glass housing
	Color	White/Black/Customization
General Parameters	Video Format	Support wmv, avi, flv, rm, rmvb, mpeg, ts, mp4, etc
	Audio Format	Support MP3, WMA, OGG
	Picture Format	Support BMP, JPEG, PNG, GIF
	Working Temperature	-10℃ - +50℃
	Working Humidity	10 ~ 90% RH, no condensation
	Power Supply	AC100-240V 50/60Hz
	Power Consumption	≤ 175W
	Standby Consumption	0.5W
	Dimension	2116*878*519mm
	Weight	N.W.:52KG, G.W.:65KG
	Mounting Brackets	Transparent double-sided display, base (base front cover, base back cover, base bracket, glass fixing plate, motherboard bracket)
	Accessory	Remote control, manual, power cord, installation guide