

Company:
Attn:
Email:
Tel:



Zhuhai Numcloud Technology Co., Ltd
No.383,Jinming Dong Road ,Jinwan,Zhuhai City,Guangdong,China
Website: www.numcloud.cn Email: sale@numcloud.cn
Tel: 008615014900716 Contact: Donna Chen

Version: 2023
Issued Date: 2023.11.06

Quotation

Small Size Constant Voltage Power Supply

Photo	Dimmable	Model	Power	Input voltage	Output voltage	Output current	Effi	Power Factor	Warranty	Material /IP	Dimension (PCB)	Dimension (with housing)	Weight
	Non	NC-06005-VL1	1-5W	85-277Vac	3.3Vdc	850mA	>75%	>0.5	3 years	Plastic (anti-fire) IP20/IP66	23*15*15mm	27*22*19mm	30g
					5Vdc	800mA							
					6Vdc	700mA							
					12Vdc	400mA							
	SET-RGB	NC-05003-VS1	3W	100—240Vac	5Vdc	0.5A	>78%	>0.5	3 years	Plastic (anti-fire) IP20/IP66	24*18*15mm	30*22*18mm	12g
	Non	NC-05003-VL1		100—240Vac	5Vdc	0.3A/Channel	>78%	>0.5	3 years		24*18*15mm	30*22*18mm	15g
		NC-12003-VL1		100—240Vac	12Vdc	0.5A	>78%	>0.5	3 years		25*18*13mm	30*22*18mm	12g
				Non	NC-05005-VL1	5W	100—240Vac	5Vdc	1A		>78%	>0.5	3 years
NC-10005-VL1	100—240Vac		10Vdc		0.4A		>78%	>0.5	3 years	29*19*16mm	38*25*18mm	15g	
NC-12005-VL1	100—240Vac		12Vdc		0.4A		>78%	>0.5	3 years	29*17*15mm	38*25*18mm	12g	
	Non	NC-05009-VL1	9W	100—240Vac	5Vdc	1.8A	>78%	>0.5	3 years	Plastic (anti-fire) IP20/IP66	40*18*16mm	50*28*20mm	12g
		NC-12009-VL1		100—240Vac	12Vdc	0.75A	>78%	>0.5	3 years		40*18*16mm	50*28*20mm	
		NC-24009-VL1		100—240Vac	24Vdc	0.37A	>78%	>0.5	3 years		46*20*15.5mm	50*28*20mm	12g
	Non	NC-12012-VL1	12W	100—240Vac	12Vdc	1A	>85%	>0.5	3 years	Plastic (anti-fire) IP20/IP66	46*20*16mm	50*28*20mm	15g
		NC-24012-VL1			24Vdc	0.5A							
	Non	NC-12020-VL1	20W	100—240Vac	12Vdc	1.6A	>83%	>0.5	3 years	Plastic (anti-fire) IP20/IP66	63*31.5*20mm	80*35*23mm	50g
		NC-24020-VL1			24Vdc	0.8A							
		NC-36020-VL1			36Vdc	0.5A							
	Non	NC-12024-VL1	24W	100—240Vac	12Vdc	2A	>83%	>0.5	3 years	Plastic (anti-fire) IP20/IP66	75*38*16mm	110*45*28mm	50g
		NC-24024-VL1			24Vdc	1A							
		NC-36024-VL1			36Vdc	1.5A							

Company:

Attn:

Email:

Tel:



Zhuohai Numcloud Technology Co., Ltd

No.383,Jinming Dong Road ,Jinwan,Zhuohai City,Guangdong,China

Website: www.numcloud.cn Email: sale@numcloud.cn

Tel: 008615014900716 Contact: Donna Chen

Quotation

Version: 2023
Issued Date: 2023.11.06

Ultra Slim Constant Current Power Supply, Isolated,Flicker-free														
PCB Photo	Photo	Dimmable	Model	Power	Input voltage	Output voltage	Output current	Effi	Power Factor	Warranty	Material /IP	Dimension (PCB)	Dimension (with plastic)	Weight
		Non	NC-15350-CL2	7-15W	90-265V	30-42Vdc	150-350mA	>85%	>0.95	3 years	Isolated, flicker-free, -20+65℃, 2KV,THD<10%	200*18*10mm	258*21*15mm	30g
		Non	NC-25600-CL2	16-24W	90-265V	30-42Vdc	380-550mA	>86%	>0.95	3 years	Isolated, flicker-free, -20+65℃, 2KV,THD<10%	230*18*11mm	258*21*15mm	30g
		Non	NC-30700-CL2	24-30W	90-265V	30-42Vdc	400-700mA	>87%	>0.95	3 years	Isolated, flicker-free, -25+50℃, THD<10%	295*18*12mm	378*24*22mm	58g
		Non	NC-401000-CL2	30-40W	90-265V	30-42Vdc	600-1000mA	>88%	>0.95	3 years	Isolated, flicker-free, -20+65℃, THD<10%	310*18*12mm	378*24*22mm	58g
		Non	NC-481200-CL2	40-48W	100-265V	28-42Vdc	800-1200mA	>88%	>0.95	3 years	Isolated, flicker-free, -20+65℃, THD<10%	310*18*12mm	378*24*22mm	83g
		Non	NC-26650-CQ2	5-26W	85-277V	21-39Vdc	200-650mA	>89%	>0.95	3 years	Isolated, flicker-free, -20+65℃, THD<10%	80*16*10mm	258*21*15mm	80g
		Non				36-60Vdc	100-500mA	>89%	>0.95	3 years		80*16*10mm	258*21*15mm	80g
		Non				54-60Vdc	100-400mA	>89%	>0.95	3 years		80*16*10mm	258*21*15mm	80g
		Non	NC-26500-CQ2	5-26W	85-277V	36-80Vdc	150-350mA	>89%	>0.95	3 years		142*18*10mm	258*21*15mm	80g
		Non				27-65Vdc	200-500mA	>89%	>0.95	3 years		142*18*10mm	258*21*15mm	80g
		TRIAC	NC-12300-CT2	6-12W	90-265V	30-50Vdc	50-300mA	>85%	>0.95	3 years	Isolated, flicker-free, -20+65℃, 2KV,THD<10%	230*17*11mm	258*21*15mm	30g
		TRIAC	NC-25600-CT2	12-25W	90-265V/305V	30-50Vdc	300-600mA	>86%	>0.95	3 years		305*18*12mm	378*24*22mm	30g
		TRIAC	NC-30700-CT2	23-30W	90-265V	30-50Vdc	400-700mA	>87%	>0.95	3 years	Isolated, flicker-free, -25+50℃, THD<10%	335*18*12mm	378*24*22mm	56g
		TRIAC	NC-401000-CT2	30-40W	90-265V	30-50Vdc	600-1000mA	>88%	>0.95	3 years	Isolated, flicker-free, -20+65℃, THD<10%	335*18*12mm	378*24*22mm	80g

TO	Company:
	Attn:
	Email:
	Tel:



Zhuhai Numcloud Technology Co., Ltd	
No.383,Jinming Dong Road ,Jinwan,Zhuhai City,Guangdong,China	
Website: www.numcloud.cn	Email: sale@numcloud.cn
Tel: 008615014900716	Contact: Donna Chen

Quotation

Version: 2023
Issued Date: 2023.11.06

Round Constant Current Power Supply, Isolated,Flicker-free

NO.	PCB Photo	Photo	Dimmable	Model	Power	Input voltage	Output voltage	Output current	Effi	Power Factor	Warranty	Material /IP	Dimension (PCB)	Dimension (with)	Weight
1			Non	NC-20300-CR1	6-20W	85-265V	20-75Vdc	280mA 300mA	>89%	> 0.5	3 years	Isolated, flicker-free, -30+55℃	Ø42*20mm	Ø55*25mm	27g
2			Non	NC-361200-CR1	18-36W	100-277V	45-80Vdc	300-600mA	>88%	>0.95	3 years	Isolated, flicker-free, -20+50℃	Ø52*25mm	Ø75*25mm	27g
							24-42V	600-1050mA							
							27-54V	700-1000mA							
							12-24Vdc	800-1200mA							
3			Non	NC-501500-CR1	40-50W	100-277V	27-38Vdc	1000mA 1100mA 1200mA 1250mA 1350mA 1400mA 1450mA 1500mA	>90%	>0.95	3 years	Isolated, flicker-free, -40+50℃	Ø70*25mm	Ø80*30mm	27g
4			Non	NC-802000-CR1	54-80W	85-300V	35-50Vdc	1200mA 1500mA 1800mA 2000mA 2400mA	>90%	>0.98	3 years	Isolated, flicker-free, -30+55℃, 抗雷抗浪涌 >4000V	Ø75*25mm	Ø95*30mm	27g

Round Constant Current Power Supply for LED and Fan, Isolated,Flicker-free

NO.	PCB Photo	Photo	Dimmable	Model	Power	Input voltage	Output voltage	Output current	Effi	Power Factor	Warranty	Material /IP	Dimension	Dimension	Weight
1			Non	NC-501200-CRF1	25-36W	85-300V	36-52Vdc	500mA 550mA 600mA 650mA	>90%	>0.95	3 years	Isolated, flicker-free, -20+55℃	52.5*52.5*25mm	Ø80*30mm	27g
							12V for fan	100mA							
2			Non	NC-501500-CRF1	36-50W	85-277V	27-36Vdc	1200mA 1250mA 1400mA 1500mA	>90%	>0.95	3 years	Isolated, flicker-free, -20+50℃	Ø68*25mm	Ø95*30mm	27g
							12V for fan	100mA							
3			Non	NC-541600-CRF1	36-54W	100-277V	27-36Vdc	1200mA 1400mA 1500mA 1600mA	>90%	>0.95	3 years	Isolated, flicker-free, -40+50℃	Ø70*25mm	Ø95*30mm	27g
							12V for fan	100-200mA							
3			Non	NC-541600-CRF1	80-120W	90-305V	30-48Vdc	3000mA 2900mA 2800mA 2700mA 2500mA 2400mA 2200mA 2100mA	>90%	>0.95	3 years	Isolated, flicker-free, -30+55℃, 抗雷抗浪涌 >4000V	Ø90*30mm	Ø105*30mm	27g
							12V for fan	100mA							

Round Constant Current Power Supply , Non-Isolated,Flicker-free

NO.	PCB Photo	Photo	Dimmable	Model	Power	Input voltage	Output voltage	Output current	Effi	Power Factor	Warranty	Material /IP	Dimension	Weight	
1			Non	NC-80600-CRN1	40-80W	180-265V	60-150Vdc	450mA 500mA 550mA 600mA	>94%	> 0.55	3 years	Non-Isolated, flicker-free, -40+55 °C	Ø45*25mm	Ø55*25mm	27
2			Non	NC-1001200-CRN1	70-100W	100-265V	45-80Vdc	800mA 900mA 1000mA 1110mA 1200mA	>93%	> 0.55	3 years	Non-Isolated, flicker-free, -25+50 °C	Ø71*25mm	Ø80*30mm	27
3			Non	NC-1501200-CRN1	80-150W	180-264V	70-160Vdc	800mA 900mA 1000mA 1110mA 1200mA	>93%	> 0.55	3 years	Non-Isolated, flicker-free, -30+50 °C	Ø71*25mm	Ø80*30mm	27