

Detail Specifications



LCD Panel	Model No	FC-65LED	FC-75LED	FC-86LED
	Screen Size	65"	75"	86"
	Screen Type	DLED		
	Resolution	3840(H)×2160(V) (UHD)		
	Color	10 bit 1.07B		
	Active Size(mm)	1428.48*803.52	1649.66*927.93	1895.04*1065.96
	Brightness	>400cd/m2		
	Contrast	4000:1 (according to panel brand)		
	Viewing Angle	178°		
	AG Glass	Tempered explosion-proof glass 3.2 mm		
	Backlight Lifetime	>50000 hours		
Electrical performance	Max Power	≤250W	≤300W	≤400W
	Standby Power	≤0.5W		
	Voltage	110-240V(AC), 50/60Hz		
Touch	Touch Technology	IR touch; 50 points in Windows 20 points in Android; HIB Free drive		
	Touch Items	Finger, Pen, any opaque objects		
	Response Speed	≤ 7ms		
	Operation System	Support Windows, Android, Mac OS, Linux		
Speakers	Power	15W*2 / 8Ω; (2.1EDR with 20 * 2 as option)		
Working Environment	Working Temperature	0℃ ~ 40℃		
	Storage Temperature	- 20℃ ~ 60℃		
	Working Humidity	10%-90% non-condensing		
Accessories	Power cable*1 pcs; Remote controller*1 pcs; Touch pen*1 pcs; QC&Warranty card*1 pcs;Wall mount brackets*1 pcs; Mobile stand ops as option			
System	Android 11.0/12.0/13.0 , 4G/8G RAM , 32G/64G/128G ROM			
I/O Interfaces	Input Ports: HDMI, LAN(RJ45), AV in(mini),USB 3.0, USB2.0, RS232 , Touch USB, OPS Slot Output Ports: SPDIF, Earphone, AV OUT, Other Ports as option: Type-C, DP,HDMI-out,RJ45-out (I/O Interfaces are different according to different Android versions.)			