

■ 产品说明:

- 导体使用镀锡绞铜线30~2000kcmil 额定温度: 105℃ 额定电压: 600V PVC 绝缘, 柔软抗老化
- 易开线和剥皮。
抗酸碱, 耐油及防潮霉性能好

应用:

- 一般商用电子, 电器及设备仪器内部连接线, 环境温度不超过105℃场合

■ PRODUCT DESCRIPTION

- Tinned stranded copper conductor ; 30~2000kcmil. Rated temperature: 105℃, rated voltage: 600 volts Flexible and long term usage. PVC material insulation.
- Easy stripping and cutting. Resistant to acids, alkalis, oils, moisture and fungi.

Application:

- For general purpose internal wiring of electronic, appliances where exposed to temperatures not Exceeding 105℃.

**■ 印字 MARKING**

AWM 1015 E330484 VW-1 105 °C 600V XX AWG B&T CABLE FT1 c. AWM I A 105°C 600V XX AWG -LF-

■ 产品结构 CABLE CONSTRUCTION

Part No.	AWG	construction No./mm	conductor diameter	insulation thickness	overall diameter	conductor resistance At 20℃	package ft/roll
型号	线规	导体结构 线数/线径	绞合直径 mm	绝缘厚度 mm	完成外径 mm	导体电阻 欧姆/KM	包装 英尺/卷
1015	10	105/0.254	3.40	0.79	5.00	3.73	
1015	12	65/0.254	2.36	0.79	4.00	6.07	
1015	14	41/0.254	1.88	0.79	3.50	9.59	
1015	16	26/0.254	1.50	0.79	3.10	15.06	
1015	18	41/0.16	1.20	0.79	2.75	22.98	
1015	20	26/0.16	0.95	0.79	2.55	38.58	
1015	22	17/0.16	0.76	0.79	2.40	60.16	
1015	24	11/0.16	0.61	0.79	2.20	88.36	