

CT02-Crosssky R70 参数表

产品图 Product Image			
White	Black	Blue	Green
			

耳机种类			Specifications		
			Headphone Type		Hook-on Open-Ear Bluetooth Headphones
蓝牙参数	蓝牙版本	V6.0	Bluetooth parameters	Bluetooth version	V6.0
	蓝牙芯片类型/型号	WQ7035MX		Bluetooth chipset	WQ7035MX
	蓝牙协议	HFP/A2DP/AVRCP		Bluetooth profile	HFP/A2DP/AVRCP
	传输范围	音乐直线/360≥15米（手捂耳7米）； 通话直线/360≥15米； 依iphone6s、华为P40为准		Operation Range	Music Playback: 15+ meters (Line-of-sight/360° coverage) ■ 7 meters when hand-covered (e.g., cupping ear) Voice Calls: 15+ meters (Line-of-sight/360° coverage)
	延迟时间	普通模式： SBC约218.6ms、AAC约288.2ms； 游戏模式： SBC约138.8ms、AAC约225.7ms(AP测试)		Latency	Standard Mode: ≈ 218.6ms (SBC) / ≈ 288.2ms (AAC) Game Mode: ≈ 138.8ms (SBC) / ≈ 225.7ms (AAC) (Tested with AP equipment)
降噪参数	降噪类型	/	Noise canceling parameters	Noise canceling type	/
	降噪频宽	/		Frequency range	/
	平衡度(dB)	/		Channel difference (dB)	/
	最大降噪深度	/		Noise Reduction Rating	/
续航	待机时间（连接状态）	约120小时	Battery life	Standby time (connected state)	120H
	通话时间（50%音量）	约8小时		Call time (50% volume)	8H
	音乐播放时间（50%音量）	SBC/AAC约13小时，LDAC约7小时		Music playback time (50% volume)	13 hours (SBC/AAC) 7 hours (LDAC)
	音乐播放时间（50%音量，搭配充电仓使用）	约52小时		Music playback time (50% volume, with use of charging case)	52 hours total
电池容量	耳机电池容量	60mAh	Battery capacity	Earbud	60mAh
	充电仓电池容量	580mAh		Charging case	580mAh
耳机充电参数	标准充电电压	5VDC	Charging parameters (Earbud)	Standard charging voltage	5VDC
	标准充电电流	48mA		Standard charging current	48mA
	充电时限	≤ 2H		Charging time	≤ 2H
	充电电压范围	5V±0.25		Charging voltage range	5V±0.25
充电盒充电参数	标准充电电压	5VDC	Charging parameters (Charging case)	Standard charging voltage	5VDC
	标准充电电流	有线充电电流约430mA+/-10%，无线充电电流215mA		Standard charging current	Wired: ~430mA (±10%) Wireless: 215mA
	充电时限	有线充≤2H，无线充约3小时(无线充Output 10w)		Charging time	Wired: ≤2 hours Wireless: ~3 hours (10W output)
	充电电压范围	5V±0.25		Charging voltage range	5V±0.25
	充电接口	USB-C		Charging port	USB-C
工作环境	工作温度	-20~55℃	Working environment	Working temperature	-20~55℃
	存储温度	-20~80℃		Storage temperature	-20~80℃
喇叭	相对湿度	5~95%RH	Speaker	Relative humidity	5~95%RH
	喇叭单元类型	跑道形 12*17mm 动圈喇叭		Speaker Type	12×17mm race-track dynamic driver
	喇叭单体阻抗	16Ω ±15%		Impedance (Ω)	16Ω ±15%
	喇叭最大输入功率	50mW		Input Power (MAX)	50mW
	频段	20Hz-20KHz		Frequency range	20Hz-20KHz
	灵敏度(dB/mW) Sensitivity (Headset)	112 ± 3dB @1kHz -10dBFS by IEC-711		Sensitivity (dB/mW)	112 ± 3dB @1kHz -10dBFS by IEC-711
	失真度	≤ 11%(230Hz), ≤ 6%(315Hz-650Hz), ≤ 3%(800Hz-5000Hz)		T.H.D	≤ 11%(230Hz), ≤ 6%(315Hz-650Hz), ≤ 3%(800Hz-5000Hz)
	平衡度(dB)	<3dB(50Hz-5KHz)		Channel difference (dB)	<3dB(50Hz-5KHz)
	最大安全声压（EN50332-2）<100dB	95dB		Sound Pressure Level (Max)	95dB
	麦克风	咪类型		MEMS Microphone	Microphone
指向性		全指向 Omni-directional	Directivity	Omni-directional	
灵敏度（dBV/Pa）		-11+3dB @1kHz 1Pa(WideBand)	Sensitivity (dBV/Pa)	-11+3dB @1kHz 1Pa(WideBand)	
频率范围（Hz）		100Hz-10KHz	Frequency range (Hz)	100Hz-10KHz	
工作电压范围（V）		1.6-3.6V	Operation Voltage Range (V)	1.6-3.6V	
消耗电流		<160 μA	Current consumption (uA)	<160 μA	
信噪比		62dB(A)	S/N Ratio	62dB(A)	
防水等级		IPX5	Waterproof Rate	IPX5	
主按键类型		触摸控制	Button type	Touch Control	
产品尺寸		单个耳机裸机重量 (g)	10g	Specifications	
	整机重量（含充电仓）	103g	Total weight (including charging case)		103g
	耳机尺寸	50.3 x 43 x 17mm	Earbud dimensions		50.3 x 43 x 17mm
	充电仓尺寸	109 x 59 x 27mm	Charging case dimensions		109 x 59 x 27mm
包装规格	包装尺寸	100 x 40 x 150mm	Packaging specifications	Package dimensions	100 x 40 x 150mm
	装箱尺寸			Carton dimensions	
	装箱数量			Quantity per carton	