

Floor Standing Digital Signage Specifiaction-K Series (32"-65")

Picture					
Model	TM01Z32LD	TM01Z43LD	TM01Z49LD	TM01Z55LD	TM01Z65LD
Display	32"	43"	49"	55"	65"
Resolution	1920*1080	1920*1080	1920*1080	1920*1080	1920*1080
Brightness	350cd			400cd	
Contrast Ratio	1200:1			1400:1	
Coloration	1.67M				
Response Time	8ms				
Viewing Angle	178°(H/V)				
CPU/Chipset	NT68676, T10, T20, RK3368, RK3188, RK3288, RK3399, J1900, Core I3, Core I5, Core I7				
Memory	Android: 1GB, 2GB / Windows: 4GB, 8GB				
Storage	Android: 8GB / Windows: 128GB				

Wifi	802.11 b/g/n				
OS	Android or Windows				
Interface	Android board: USB*2, RJ45*1, SD*1, HDMI*1/ Windows board: USB*4, RJ45*1, HDMI*1, VGA*1				
Touch	Non-touch/ Capacitive Touch/ Infrared Touch				
Speaker	2PCS Built-in Speakers				
Power Supply	100-240VAC, 50/60Hz				
Audio Format	MP3,WMA,WAV,etc				
Video Format	AVI,MP4,3GP,MVB,WMA,MTV,MOV,MPG,MKV,etc				
Image Format	JPGE,PNG,BMP,GIF,etc				
System Mangement Mode	Centralization of management,Group Management, Multi-user Management, Remote Control, Time Switch				
Remote Control Mode	Remote Auto Time Switch, Remote Auto Update, Remote Monitoring				
System Playing Mode	Support Loop, Time, Spot Announcement				
Security	Softdog, Log In Pass Word, Control Pass Word, Authority				
Operation Temperature	-10-50℃				
Color	Black/White/Silver/Customized				
Dimension	1037.9*758*434	1061.2*1010.8*482.8	1076.76*1140.9*482.8	1097.68*1284.9*482.8	1124.46*1504*482.8
Accessory	User's Manual,Power Cord, Lag Spike,Wrench,Key,Wifi Antenna,etc				

Packing	Wooden Case, Carton, Flight Case, etc
---------	---------------------------------------