



ED424H65

Features & Benefits

- 4U 650mm depth, ideal for IDC/High Performance Computing Server/NAS Server
- Support Extended (12"x13"),(12"x10.5") ,(12"x9.6") M/B
- Support Standard ATX power/ Redundant 2+1 power
- Optional front VGA port for on-site monitoring
- Modular design in HDD cage/front fan/backplane for easy maintenance
- Fully utilized space to support 24 x 3.5" HDD

Specification

Order Code		Generality	
ED424H65		Metal Material	SGCC
Description		Metal Thickness	1.2 mm
4U 650mm depth,Hot-swap 24x 3.5"HDD		Metal Material Type	ABS
M/B Form Factor		Expansion Slots	
(12"x13"),(12"x10.5"),(12"x9.6")		FF	7
Processor		System Cooling(Hot-Swap)	
DP Xeon(Intel),DP Opteron(AMD)		Middle	4 x 8025 mm hot-swap
Core(Intel)		Rear	2 x 8025 mm
Support Backplane		Rear Window	
MINISAS		Standard	
Chassis Dimension		Front Panel	
D x W x H (mm)	650x430x176	Front Control	Power On/Off
D x W x H (inch)	25.6"x16.9"x7.0"		System Reset
			Alarm Reset
Drive Bay		Indicator	Power LED (x1)
Hot-Swap 3.5" and 2.5"	24 (Mini SAS)		HDD Activity LED (x1)
CD-ROM			LAN Activity LED (x2)
			Fan / Power Failure LED
Power Supply		Ports	USB2.0 x 2
Standard ATX power/ Redundant 2+1 power			VGA (option)
		Shipping Information*	
		Net Weight (Chassis Only)	15 Kg
		Gross Weight (w/Packing)	16.5 Kg
		Cubit Feet	0.147CBM
		Container Information	20'
			40'
			40'H

Package Contain

Part Category	Qty.	Description
Chassis	1	4U chassis base with Fans
Backplane	6	4 x 3.5"HDD ports MINISAS backplane
Parts Pack	1	Screw Pack,Bracket