

PARAMETER OF PRODUCTS:

DESCRIPTION	PARAMETERS	PRODUCTS LIST
BUTTON SWITCH	10A 250V~	Switch in F2000, F3000, F5000, F6000, F8000 S1000, S2000, S3000, S5000, S6000, S8000
SOCKET WITHOUT EARTH	10A 250V~	Socket in F2000, F3000, F5000, F6000, F8000 S1000, S2000, S3000, S5000, S6000, S8000
SOCKET WITH EARTH	16A 250V~	Socket in F2000, F3000, F5000, F6000, F8000 S1000, S2000, S3000, S5000, S6000, S8000
EXTENSION SOCKET WITHOUT EARTH	10A 250V~	Extension Socket in E2000, E5000, E6000, E8000, E9000 Series
EXTENSION SOCKET WITH EARTH	16A 250V~	Extension Socket in E2000, E5000, E6000, E8000, E9000 Series
PLUG WITHOUT EARTH AND ADAPTOR	10A 250V~	Plug and Adaptor in P7000, P8000 Series
PLUG WITH EARTH	16A 250V~	Plug and Adaptor in P7000, P8000 Series
LAMP HOLDER	3A 250V~ 600W	Lamp holder in H5000, H6000 Series`
DIMMER SWITCH	3A 250V~ 650W	Dimmer Switch in F2000, F3000, F5000, F6000, F8000 Series

EXPLANATION OF MATERIAL:

Abbreviation	Full name	Character
ABS	Acrylonitrile Butadiene Styrene	The overall performance is better: high impact strength, chemical stability, good electrical properties ABS plastic disadvantages: low thermal deformation temperature, flammable, poor weather resistance.
PP	Polypropylene	excellent rigidity, heat resistance, impact strength
PC	Polycarbonate	easily worked, molded, and thermoformed high impact-resistance heat-resistant and flame-retardant properties, high-stability
PA NYLON	Polyamide	good elasticity, resistant to heat good resistance to acids, and is resistant to alkali

TERMS AND CONDITIONS:

Terms and Conditions	FOB Ningbo or Shanghai
Payment Terms	T/T or L/C
Delivery Terms	30 Days after Confirmation