



SPECIFICATIONS :

Voltage Rating: 100V AC / DC
Current Rating: 2A AC / DC
Withstanding Voltage: 500V AC/minute
Temperature Range: -25°C~+85°C
Insulation Resistance: 500MΩ Min.
Contact Resistance: 30mΩ Max.
*Suitable LDZY A1505 series Terminal
*Mates with LDZY A1505 series Wafer

Material:

Material: PA66 UL94V-0,
Color: Natural

A1505 H - 2NP - N0 NA
① ② ③ ④ ⑤

- ① Series No.
- ② Housing Type: H-Housing
- ③ Pin No.: 210=2*05PIN....
- ④ Material: N0-PA66, UL94V-0
- ⑤ Color: NA-Natural

CSG PART NO.	Dimension mm			
	A	B	C	D
2*05	7.50	6.00	11.20	9.30
2*06	9.00	7.50	12.70	10.80
2*07	10.50	9.00	14.20	12.30
2*08	12.00	10.50	15.70	13.80
2*09	13.50	12.00	17.20	15.30
2*10	15.00	13.50	18.70	16.80
2*11	16.50	15.00	20.20	18.30
2*12	18.00	16.50	21.70	19.80
2*13	19.50	18.00	23.20	21.30
2*14	21.00	19.50	24.70	22.80
2*15	22.50	21.00	26.20	24.30
2*16	24.00	22.50	27.70	25.80
2*17	25.50	24.00	29.20	27.30
2*18	27.00	25.50	30.70	28.80
2*19	28.50	27.00	32.20	30.30
2*20	30.00	28.50	33.70	31.80

						一般公差 GENERAL TOLERANCE	LDZY[®] Electronics 东莞市蓝雁电子有限公司 DongGuan LDZY Electronics CO.,LTD.				料号 PART NO A1505H-2NP-N0NA			
						. X ±0.3 . XX ±0.2 . XXX ±0.1					品名 TITLE 1.50mm Pitch Single Row Housing			
日期 DATE	旧版次 OLD REV	新版次 NEW REV	变更内容 DESCRIPTION	审核 CHK	核准 APPD	角法 PROJECT 	周立鸿	兰 雄	陆 波	2022/04/13	单位 UNIT mm	比例 SCALE 1/1	图号 NUMBER LDZY-8115 LDZY-8713	版次 REV A