



SGS CE



South African Socket

- Rated voltage: 250V
- Rated current: 16A
- Size: 45*45*33.7mm
- Color: White/Black
- Material: PC



XJY-QB-50 (Smooth Surface)

XJY-QB-50K (Pitted Surface)



Indian socket

- Rated voltage: 250V
- Rated current: 6A
- Size: 45*45*24.35mm
- Color: White/Black
- Material: PC



XJY-QB-94 (Smooth Surface)

XJY-QB-94K (Pitted Surface)

Multi-functional socket

- Universal socket
- Rated voltage: 250V
- Rated current: 10A
- Size: 45*45*37.2mm
- Color: White/Black
- Material: PC



XJY-QB-29 (Smooth Surface)

XJY-QB-29K (Pitted Surface)

*Suitable for EU(type F), UK(type G), IT(type L) and CN plug

Multi-functional socket

- Rated voltage: 250V
- Rated current: 10A
- Size: 45*45*28mm
- Color: White/Black
- Material: PC



XJY-QB-51 (Smooth Surface)

XJY-QB-51K (Pitted Surface)

Five holes socket

- Rated voltage: 250V
- Rated current: 10A
- Connection mode: Screw
- Size: 45*45*32.6mm
- Color: White/Black
- Material: PC



XJY-QB-44 (Smooth Surface)

XJY-QB-44K (Pitted Surface)

Five holes socket

- Rated voltage: 250V
- Rated current: 10A
- Connection mode: Welding
- Size: 45*45*31mm
- Color: White/Black
- Material: PC



XJY-QB-44A