

HS60

5G Smart Handheld Terminal



Features

N60 industrial-grade IoT handheld terminal, 5.99-inch full screen, Android 10.0 system, supports 5G Netcom, and runs smoother.

Warehousing, logistics, library, retail and other industries.

-  Android 10.0
-  5.99 inch IPS Screen
-  Cortex-A76/A55 Octa-core 64-bit CPU,2.0GHz
-  4GB+64GB(Optional 6GB+128GB)
-  4200mAh Removable Battery
-  GPS,Galileo,Glonass,Beidou
-  NFC : 2-5cm reading distance
-  Fingerprint recognition
-  1D/2D Barcode Scanner (Optional)
-  Camera: 16MP (Rear) 5MP (Front)

Parameters

Pertformance	Octa core
CPU	Cortex-A76/A55 Octa-core 64-bit 2.0GHz high-performance processor
RAM+ROM	4GB+64GB(Supports up to 6GB+128GB)
System	Android 10.0
Dimensions	164.5mm×79.4mm×12.3mm

Weight	<265g (Depends on device function configuration)
Display	5.99 inches IPS color display,resolution 720*1440
TP	Supports multi-touch ,Supported gloves and wet hands
WLAN	Dual frequency 2.4GHz/5GHz, support IEEE 802 a/b/g/n/ac protocol
WWAN	2G: GSM (Mobile/Unicom), CDMA (Telecom)
	3G: WCDMA (Unicom), CDMA2000 (Telecom), TD-SCDMA (Mobile)
	4G: TD-LTE (mobile), FDD-LTE (unicom, telecommunications)
	5G: Mobile 5G, China Unicom 5G, Telecom 5G
Bluetooth	Support BT 5.0 ,Transmission distance 5-10 meters
GNSS	Support Gps, Galileo, Glonass, Beidou
Communication interface	Type-C USB x 1, OTG
Battery capacity	Rechargeable polymer battery (3.8V4200MAh)Standby time >350 hours
	Working time > 12 hours,Support fast charge, removable battery,Charging time < 1.5H,(Use the standard fast charging source adapter and data cable)
Expansion Card slot	Nano SIM card
Keypad	Power button, Volume +/- button,Scan button × 2Handle scan button × 1
Sensors	Gravity sensor, Light sensor, Proximity sensor,Gyroscope, electronic compass
NFC	Support ISO14443A/B, 15693 agreement,Frequency:13.56MHz,Read distance:2cm-5cm
2D Imager scanne	Honeywell N6703
2D Symbologies	PDF417, Micro PDF417,GS1 Composite,Aztec Code,Data Matrix,QR Code, Micro QR Code,Maxicode,Hanxin Code,etc.
Camera	16MP HD camera, front camera 5MP, Support auto focus,camera flash , Anti-shake, Macro shooting
Operating temperature	-20°C-55°C
Storage temperature	-40°C-70°C
Environment humidity	5%RH--95%RH(no condensation)
Protection	IP66
Fall/Rolling test	6 sides Supports 1.5 meters drops and 30 times to the concrete with
	in the operating temperature,500×0.5m rolling for 6 sides



Shenzhen Effon Ltd

Tel: 86 0755 23229300

Fax : 86 0755 23229300

Email : amina@effon.com

Website : www.effon.com