

DS TYPE(Deep Bottom Bucket)



Use of advice

- Suitable for Gravity discharge and mixed discharge.
- A, B, C size show on the followed table are HDPE bucket size, Nylon bucket size will increase about 2%
- Recommend using $(Z-Y) \times 10\%$ as usable capacity.

Model	Length A (mm)	Proj. B (mm)	Distance C (mm)	Distance Down D (mm)	Center to Center E (mm)	Number of holes	Hole Diameter (mm)	Capacity (X-Y) (L)	Capacity (Z-Y)+10% (L)	Capacity (Z-Y) (L)	Note
DS0705	78	55	71	20	40	2	7	0.16	0.07	0.06	Fitting holes and hole diameter can be customized
DS0807	90	75	64	20	50	2	7	0.25	0.15	0.14	
DS1009	104	90	82	24	50	2	7	0.40	0.29	0.26	
DS1109	116	90	82	25	60	2	7	0.42	0.30	0.27	
DS1307	130	75	80	25	60	2	7	0.40	0.24	0.22	
DS1309	130	90	80	25	60	2	7	0.50	0.25	0.23	
DS1311	134	115	94	35	60	2	7	0.65	0.50	0.45	
DS1411	145	110	96	35	60	2	7	0.75	0.59	0.54	
DS1508	152	84	78	18	76	2	7	0.47	0.35	0.32	
DS1511	150	115	94	35	80	2	7	1.07	0.90	0.80	
DS1612	165	124	110	40	90	2	7	1.10	0.81	0.74	
DS1613	164	139	124	40	90	2	9	1.40	1.12	1.02	
DS1812	188	125	115	40	120	2	9	1.20	0.73	0.66	
DS1814	188	140	127	40	120	2	9	1.70	1.32	1.20	
DS2010	202	102	98	20	120	2	7	1.00	0.83	0.75	
DS2014	206	140	117	40	120	2	9	1.65	1.05	0.95	
DS2312	235	125	118	40	120	2	9	1.70	1.32	1.20	
DS2314	237	142	127	40	85	3	9	2.10	1.60	1.45	
DS2316	236	164	148	45	85	3	9	2.88	1.85	1.68	
DS2511	250	114	115	25	125	2	7	1.50	0.99	0.90	
DS2616	268	162	145	45	90	3	9	3.15	2.30	2.09	
DS2812	282	126	116	40	100	3	9	2.00	1.63	1.48	
DS2814	285	140	127	40	100	3	9	3.00	2.20	2.00	
DS2816	282	168	149	45	100	3	9	3.60	2.75	2.50	
DS2823	289	230	190	55	100	3	9	6.70	4.85	4.41	
DS2916	297	170	155	45	110	3	9	4.00	2.77	2.52	
DS2919	295	197	178	50	75	4	9	5.80	4.72	4.29	
DS3114	312	147	146	45	80	4	9	3.26	2.30	2.09	
DS3116	313	168	154	45	85	4	9	4.40	3.09	2.81	
DS3118	312	190	170	45	85	4	9	4.80	3.47	3.15	
DS3121	316	218	195	55	85	4	9	7.60	6.20	5.56	
DS3518	358	190	174	50	95	4	9	5.80	4.50	4.10	
DS3621	365	220	200	55	95	4	9	8.50	7.10	6.45	
DS4118	419	190	178	50	85	5	9	8.40	5.64	5.13	
DS4121	418	222	200	55	85	5	9	10.40	8.77	7.97	
DS4621	460	220	196	55	95	5	9	12.00	9.80	8.90	
DS4822	480	223	210	68	76	6	11	13.00	9.24	8.40	
DS5121	519	228	203	55	90	6	11	13.11	11.66	10.60	