



## PRODUCT GALLERY

### 孚賽能源科技有限公司

VCELL POWER CO.,LTD

### Li Ion Battery

Model	Nominal Voltage(V)	Nominal Capacity(mAh)	Diameter(mm)	Height (mm)	Weight(g)
ICR10440	3.7	350	10.2	44.5	10
ICR14250	3.7	350	14.2	25.5	10
ICR14650	3.7	1100	14.2	65.5	25
ICR14500	3.7	800	14.2	50.5	22
ICR16430	3.7	600	16.2	43.5	17
ICR17335	3.7	600	17.2	33.7	17
ICR18500	3.7	1500	18.2	50.5	33
ICR18650	3.7	2200	18.2	65.5	43
	3.7	2400	18.2	65.5	43
	3.7	2500	18.2	65.5	44
	3.7	2600	18.2	65.5	45
	3.7	2800	18.2	65.5	47
ICR26650	3.7	5000	26.2	65.5	95

Lithium-ion battery or Li-ion battery here refers to the lithium cobalt oxide (LiCoO<sub>2</sub>) based technology rechargeable battery, in which lithium ions move from the negative electrode to the positive electrode during discharge and back when charging. They are one of the most popular types of rechargeable batteries for portable electronics, with a high energy density, tiny memory effect, and low self-discharge less than 2.0%/month.

#### Specifications

Nominal cell voltage	3.7V
Voltage limits	2.75-4.2V
Specific energy	100-265 W·h/kg
Energy density	250-693 W·h/L
Time durability	> 5 years
Cycle durability	>700 cycles at 80%DOD
Work temperature range	-20°C-60°C
Self discharge rate	<2%/month
Typical application	Portable electronics, solar application, EV

Rm.2-308, PengChengZhongJun Compass Innovation Industrial Park, BaoAn District, ShenZhen, PR.China 518100  
 Web: [www.vcellpower.com](http://www.vcellpower.com) Tel: +86 0755-23722075 Email: [info@vcellpower.com](mailto:info@vcellpower.com)

### Li Ion Battery



Rm.2-308, PengChengZhongJun Compass Innovation Industrial Park, BaoAn District, ShenZhen, PR.China 518100  
 Web: [www.vcellpower.com](http://www.vcellpower.com) Tel: +86 0755-23722075 Email: [info@vcellpower.com](mailto:info@vcellpower.com)