

Model	SR155-C10	SR235-C10	SR265-C10	SR365R-W10	SR400R-W10
Crowd System					
Line Pull	160kN	270kN	275kN	360kN	380kN
Stroke	4200mm	5000mm	5000mm	9000/18000mm	9000/18000mm
Main Chassis					
Base Engine	D06FR	Top brand 6UZ1	Top brand 6UZ1	Top brand 6WG	Top brand 6WG1
Emission Regulation	COM 3	COM 3	COM 3	COM 3	COM 3
Engine Power	147/2100kW/rpr	257/2000kW/rpr	257/2000kW/rpr	300/1800kW/rpr	300/1800kW/rpr
Main Winch					
Line Pull	160kN	270kN	275kN	360kN	380kN
Max. Line Speed	80m/min	70m/min	80m/min	65m/min	70m/min
Rope Diameter	26mm	32mm	32mm	36mm	36mm
Overall Machine					
Operating Weight	48T	81T	85T	131T	137T
Overall Height	18590mm	22870mm	23870mm	27105mm	27105mm
Transport Height	3265mm	3660mm	3685mm	3575mm	3575mm
Transport Width	3140mm	3540mm	3540mm	3530mm	3500mm
Pile					
Max. Pile Depth	56/44m	68/54m	73/58m	100/65m	106/87m
Max. Pile Diameter	1500mm	2000mm	2200mm	2500/2200mm	2500/2200mm
Rotary Drive	155KN	210KN	230KN	340KN	350KN
Crowd Force					
Max. Output Torque	155kN·m	235kN·m	265kN·m	365kN·m	400kN·m
Speed of Rotation	5~35rpm	5~27rpm	5~25rpm	5~23rpm	5~22rpm