

	
Product Model	XA150
Input Voltage	DC 12V
Working Voltage	DC10V-15.5V
Input Current	12.5A
Conversion Efficiency	>85%
Continuous Output Power	150W
Peak Power	300W
Output Voltage	AC 100V-120V/210-240V
Output Frequency	50Hz-60Hz
Output Current	0.68A
Output Waveform	Modified Sine Wave
Temperature Protection	$\geq 70^{\circ}\text{C}$
Operating Temperature	$0^{\circ}\text{C} \sim 40^{\circ}\text{C}$
Cooling Method	Wind Cooling (start up when power on)
Buzzer Alarm	No
Fuse	10A*1+15A*1
Low Voltage Turn Off	$10 \pm 1\text{V}$
High Voltage Turn Off	$15 \pm 1\text{V}$
Fault Indicator	Under Voltage/Over Voltage: LED Red Light, Automatic Recovery
	Overload: LED Red Light
	Over temperature: LED Red Light, Automatic Recovery
	Short Circuit: LED Red Light, Automatic Recovery
	Input Reverse:Fuse Blown
Net Weight	0.42kg
Gross Weight	0.645kg
Overall Dimension	15*10.2*5.7cm
Package Dimension	20*10.7*6.7cm
Carton Dimension	69*41.5*23.6CM 40 piece/carton