

T-3040B Technical Specifications

Mechanical and Electrical Parameter				
Interface	USB			
Input Voltage	DC 5V±10%			
Scan Performance Parameter				
Sensor	CCD (2500dpi)			
Scan speed	300times/s			
Scan mode	Manual, Auto-sense, Continuous scanning			
Indicator	buzzer, light (LED)			
Scan depth	Tested Code		Minimum	Maximum
	10mil EAN13		5CM	45CM
	15mil EAN13		13CM	28CM
	40mil EAN13		20CM	90CM
Print Contrast	30%			
Resolution	≥3mil/0.076mm			
Decode Capabilities	UPC-A, UPC-E, EAN-8, EAN-13, ISSN, ISBN, Code 128, GS1-128, ISBT 128, Code 39, Code 93, Code 11, Interleaved 2 of 5, Matrix 2 of 5, Industrial 2 of 5, Standard 2 of 5 (IATA), Codabar (NW-7), Plessey, MSI Plessey, RSS, China Post, etc.			
Connectivity	USB cable, Bluetooth, 2.4Ghz wireless			
Transmission distance	Bluetooth: 10 meters in open area 2.4Ghz wireless: 30 meters in open area			
Storage capacity	16M			
Battery capacity	rechargeable battery 2200mAH			
Environmental Parameter				
Working temperature	0℃ - 50℃ (32 ℉ - 122℉)			
Storage temperature	-20℃ - 70℃ (-4℉ - 158℉)			
Humidity	5%-95% (Non-condensing)			