

| Model                      | SP06B SERIES For Euro, AU Type                                            |  |
|----------------------------|---------------------------------------------------------------------------|--|
| Electric rated             | 10A, 250Vac, 3680Watts                                                    |  |
| Number o outlets           | 6                                                                         |  |
| Grounded outlet            | 6                                                                         |  |
| Socket types               | German / French / Italy / Australia                                       |  |
| Surge Energy Joules Rating | 630Joules / (1860Joules for USA version)                                  |  |
| Cable                      | 100% copper H05VV-F 3G x 1.0mm <sup>2</sup> x 1.5meter, 3G, with grounded |  |
| Surge Lines protected      | 3line(L-N, L-G, N-G)                                                      |  |
| Surge light indicator      | Yes                                                                       |  |
| Ground light indicator     | Yes                                                                       |  |
| Circuit Breaker in Amp     | 10A, individual circuit breaker                                           |  |
| Response time              | <1 nanosecond                                                             |  |
| Master Switch              | On/Off Rocker switch                                                      |  |
| EMI/RFI filtering          | 100Khz-20Mhz                                                              |  |
| Attenuation                | Up to 30dB                                                                |  |
| Maximum spike current      | 19500Amps                                                                 |  |
| Maximum voltage in volt    | 500V                                                                      |  |
| Maximum Spike Voltage      | 6000V                                                                     |  |
| Wall mountable             | Yes                                                                       |  |
| Tel/Fax/Modem protection   | 1 in 2 out RJ11 / RJ45 protection connector (Optional)                    |  |
| TV protectoin(coaxial)     | 1 in 1 out Coaxial protection connector (Optional)                        |  |
| USB charger                | DC 5V 2.4A (2 Ports); DC 5V 3.1A (2 Ports) (Optional)                     |  |
| Product color              | Black, Grey, White                                                        |  |
| Material                   | PC94V0 fire-proof, inflammable plastic                                    |  |
| Warranty                   | More than 3years under normal use                                         |  |

| Special Specification  | UK Type                                                                                      | USA Type                                                       |
|------------------------|----------------------------------------------------------------------------------------------|----------------------------------------------------------------|
| Electric rated         | 13A, 250Vac, 3680Watts                                                                       | 15A, 125Vac                                                    |
| Cable                  | 100% copper H05VV-F 3G x 1.0mm <sup>2</sup> x 1.5meter, 3G, with grounded, BS plug with fuse | 100% copper SJT16AWG 3G x1.5meter, 3G, with grounded, USA plug |
| Circuit Breaker in Amp | 13A, individual circuit breaker                                                              | 15A, individual circuit breaker                                |