

产品型号/Model	GX-PH5	GX-PH6. 25	GX-PH8	GX-PH10	GX-PH15	GX-PH20
物理点间距Pixel pitch单位: mm	5mm	6.25mm	8mm	10mm	15mm	20mm
灯珠型号Lamp bead model	金线1313灯驱合	金线1313灯驱合	金线1313灯驱合	金线1313灯驱合	金线2121灯驱合一	金线2121灯驱合一
发光点颜色color	1R1G1B	1R1G1B	1R1G1B	1R1G1B	1R1G1B	1R1G1B
像素密度pixel density单位px/m²	40000px/m²	25600px/m²	15625px/m²	10000px/m²	4356px/m²	2500px/m²
模组尺寸Module Size	1000mm*320mm	1000mm*400mm	1000mm*400mm	1000mm*400mm	990mm*390mm	1000mm*400mm
通透率Tranparency	75%	80%	85%	90%	95%	98%
刷新率refresh rate单位hz	≥3840	≥3840	≥3840	≥3840	≥3840	≥3840
重量Weight单位kg/m²	4kg/m²	4kg/m²	4kg/m²	4kg/m²	4kg/m²	4kg/m²
最大视角viewing angle	160°	160°	160°	160°	160°	160°
供电电压(V) Supply Voltage	5	5	5	5	5	5
平均功耗(单位w/m²) Average Power	≤240w/m²	≤200w/m²	≤200w/m²	≤200w/m²	≤200w/m²	≤200w/m²
最大功耗(单位w/m) Maximum power consumption	≤800w/m²	≤600w/m²	≤600w/m²	≤600w/m²	≤600w/m²	≤600w/m²
白平衡亮度(单位cd/m²) White balanced brightness	≤2000cd/m²	≤2000cd/m²	≤2000cd/m²	≤2000cd/m²	≤2500cd/m²	≤2500cd/m²
工作温度℃ operation temperature	-22℃-55℃	-22℃-55℃	-22℃-55℃	-22℃-55℃	-22℃-55℃	-22℃-55℃
驱动方式	静态	静态	静态	静态	静态	静态
平均无故障时间 mean time between failures	≥6500	≥6500	≥6500	≥6500	≥6500	≥6500
寿命/life	100000	100000	100000	100000	100000	100000
防护等级 Protection class	IP43	IP43	IP43	IP43	IP43	IP43