



Shenzhen Richerlink Communication Technology Co.,Ltd

Add:703 Room, Building W1-A,High-tech Industrial Park, Shenzhen, China

Tel:86 755 26525810 Email:cary@richerlink.com [Http://www.richerlink.com](http://www.richerlink.com)

Item		ANS4003W
Standards compliance		HomePlug AV, IEEE 802.3u, IEEE 802.1q, IEEE 802.1x, IEEE 802.11b/g/n
Ports	WAN	1 Thread Cable Port
	LAN	3 10/100M RJ45 Ports
	TV	1 CATV Coaxial Port
WiFi	Operation Arrange	2.4~2.4835GHz
	Transmission Speed	Up to 150M
	Operation Channels	13
	Data Modulation	DBPSK,DQPSK,CCK, OFDM(BPSK/QPSK/16-QAM/64-QAM)
	Transmission Distance	60 meters max(Indoor)
	RF Power	20dBm EIRP
	Antenna	3dBi detachable HG omni antenna
EoC	Solution	Qualcomm 6400
	Output Power	≥110dBuV
	Modulation Mode	OFDM
	Transmission Speed	Physical Layer:200Mbps MAC Layer:100Mbps
	Operation Frequency	7.5-30MHz
	RF Impedance	75 Ohm
CATV RF	Bandwith	47-1000MHz
	Return Loss	>16dB
	Insert Loss	≤1dB
LED	WAN	WAN Lighting: link / Blink: data transmission
	LAN	LAN Lighting: link / Blink: data transmission
	Other	POWER(on/off) / EOC(initialization status)/ Wireless(on/off)
Size(LxWxH)		180(mm)*110(mm)*31(mm)
Operation Environment		Operation Temperature: -25~55 °C Storage Temperature: -40~70 °C Operation Humidity: 10%~90% non-condensing Storage Humidity: 10%~95% non-condensing
Power Adaptor		DC 12V/10W

