

UL3173

Low Halogen Crosslinked Wire 低卤交联线

产品说明

- 额定温度:125℃
- 额定电压:600V
- 参考标准:UL758,UL1581,CSA C22.2No.210.2
- 导体使用单支或绞合 26~9 AWG 镀锡或裸铜
- XLPE 绝缘,符合ROHS 环保标准
- 通过UL VW-1、CSA FT1 阻燃测试
- 绝缘厚度均匀、易裁线、易剥皮
- 用于一般电子、电器设备内部连接线

PRODUCT DESCRIPTION

- Rated temperature: 125℃
- Rated voltage: 600V
- Reference standard: UL758,UL1581,CSA C22.2No.210.2
- Solid or stranded ,tinned or bare copper conductor 26~9 AWG
- XLPE insulation ,comply with ROHS environmental standard
- Passes UL VW-1,CSA FT1 flame test
- Uniform insulation thickness to ensure easy stripping and cutting
- For general purpose internal wiring of appliance



印字 MARKING

AWM 3173 E330484 VW-1 125℃ 600V XXAWG B&T CABLE c AWM I A FT1 125℃ 600V XXAWG

产品结构 CABLE CONSTRUCTION

编号	导体 CONDUCTOR			绝缘 INSULATION	完成外径Overall diameter (mm)		最大导体电阻 MAX. COND. RESIS TANCE Ω /km, (20℃, DC)	参考 重量 Approx. weight (g/m)	参考 包装 Standard packing (m)
	规格 SIZE	构造 CONSTRUCTIO N (No. /mm)	外径 DIA (mm)	厚度 THICKNESS (mm)	标准Standard	公差 Tolerance			
31732607XX	26	7/0.16	0.48	0.79	2.05	±0.1	150	5.7	610
31732601XX	26	1/0.40	0.40	0.79	2.00	±0.1		4.8	
31732411XX	24	11/0.16	0.61	0.79	2.20	±0.1	94.2	7	610
31732407XX	24	7/0.20	0.60	0.79	2.20	±0.1			
317324070SXX	24	7/0.20 0S-1	0.60	0.79	2.20	±0.1			
31732401XX	24	1/0.51	0.51	0.79	2.10	±0.1	60.16	6.4	610
31732217XX	22	17/0.16	0.76	0.79	2.40	±0.1			
31732207XX	22	7/0.254	0.76	0.79	2.40	±0.1			
317322070SXX	22	7/0.254 0S-1	0.76	0.79	2.40	±0.1			
31732201XX	22	1/0.64	0.64	0.79	2.25	±0.1	38.58	7	610
31732026XX	20	26/0.16	0.94	0.79	2.55	±0.1			
31732010XX	20	10/0.254	0.94	0.79	2.55	±0.1			
31732007XX	20	7/0.32	0.94	0.79	2.55	±0.1			
31732001XX	20	1/0.813	0.813	0.79	2.40	±0.1			
31731841XX	18	41/0.16	1.20	0.79	2.75	±0.1	22.98	14.64	610
31731816XX	18	16/0.254	1.20	0.79	2.75	±0.1			
31731801XX	18	1/1.024	1.024	0.79	2.65	±0.1			
31731626XX	16	26/0.254	1.50	0.79	3.10	±0.15	15.06	20.68	610
31731601XX	16	1/1.29	1.29	0.79	2.90	±0.1			
31731441XX	14	41/0.254	1.90	0.79	3.50	±0.15	9.59	29.5	305
31731265XX	12	65/0.254	2.36	0.79	3.95	±0.15	6.07	43	305
317310105XX	10	7/15/0.254	3.40	0.79	5.00	±0.20	3.75	69.4	305
31731065XX	10	65/0.32	3.00	0.79	4.60	±0.15		64.4	

备注: XX代表颜色, 01黑色02白色03灰色04橙色05绿色06红色07蓝色08黄色09棕色10紫色11粉色; 双色线用4位表示, 前面部分为主色, 例如白/黑, 0201