



SHENZHEN TEEJOIN TECHNOLOGY CO.,LTD

Add: Building A1, Mingjun industrial park,Dalang Street,LongHua new District Shenzhen




Contact: Allen 0086 18123906130
Email: allenzhao@teejoin.com


Buyer:

Contact:

Add:

add:

No.	Description	Item No.	Product photo	Specification	Sample	100 pcs	1000 pcs	
	K52S Series US switch (Touch Glass plastic frame)							
1	1 gang switch	ZUSK52S-L1D		size:120*70mm white/black/gold	\$11.35	\$10.83	\$10.32	
2	2 gang switch	ZUSK52S-L2D		size:120*70mm white/black/gold	\$11.87	\$11.33	\$10.79	
3	3 gang switch	ZUSK52S-L3D		size:120*70mm white/black/gold	\$12.40	\$11.83	\$11.27	
4	4 gang switch	ZUSK52S-L4D		size:120*70mm white/black/gold	\$13.10	\$12.50	\$11.90	
5	Scenario switch	ZUSK52S-S1D		size:120*70mm white/black/gold	\$13.10	\$12.50	\$11.90	
6	Curtain switch	ZUSK52S-C1D		size:120*70mm white/black/gold	\$11.87	\$11.33	\$10.79	
7	Dual curtain switch	ZUSK52S-C2D		size:120*70mm white/black/gold	\$13.10	\$12.50	\$11.90	
8	Non neutral 1 gang switch	ZUSK52S-L1S		size:120*70mm white/black/gold	\$12.15	\$11.63	\$11.12	
9	Non neutral 2 gang switch	ZUSK52S-L2S		size:120*70mm white/black/gold	\$12.67	\$12.13	\$11.59	
10	Non neutral 3 gang switch	ZUSK52S-L3S		size:120*70mm white/black/gold	\$13.20	\$12.63	\$12.07	
11	Non neutral 4 gang switch	ZUSK52S-L4S		size:120*70mm white/black/gold	\$13.90	\$13.30	\$12.70	
	M62S series US switch (Touch Glass metal frame)							
12	1 gang switch	ZUSM62S-L1D		size:120*70mm white/black/gold		\$12.85	\$12.33	\$11.82
13	2 gang switch	ZUSM62S-L2D		size:120*70mm white/black/gold	\$13.37	\$12.83	\$12.29	
14	3 gang switch	ZUSM62S-L3D		size:120*70mm white/black/gold	\$13.90	\$13.33	\$12.77	
15	4 gang switch	ZUSM62S-L4D		size:120*70mm white/black/gold	\$14.60	\$14.00	\$13.40	
16	Scenario switch	ZUSM62S-S1D		size:120*70mm white/black/gold	\$14.60	\$14.00	\$13.40	

17	Curtain switch	ZUSM62S-C1D		size:120*70mm white/black/gold 	\$13.37	\$12.83	\$12.29
18	Dual curtain switch	ZUSM62S-C2D		size:120*70mm white/black/gold	\$14.60	\$14.00	\$13.40
19	Non neutral 1 gang switch	ZUSM62S-L1S		size:120*70mm white/black/gold	\$13.65	\$13.13	\$12.62
20	Non neutral 2 gang switch	ZUSM62S-L2S		size:120*70mm white/black/gold	\$14.17	\$13.63	\$13.09
21	Non neutral 3 gang switch	ZUSM62S-L3S		size:120*70mm white/black/gold	\$14.70	\$14.13	\$13.57
22	Non neutral 4 gang switch	ZUSM62S-L4S		size:120*70mm white/black/gold	\$15.40	\$14.80	\$14.20
23	RGB bulb	A19-E27-E-1PACK		LED A19-E27 9W RGBCW EU (220V)	\$6.00	\$5.56	\$5.12
24	RGB bulb	A19-E26-A-1PACK		LED A19-E26 9W RGBCW US (120V)	\$6.00	\$5.56	\$5.12
25	RGB bulb	GU10-A-1PACK		GU10 RGBCW 3.5W	\$7.00	\$6.56	\$6.12
26	RGB bulb	C37-A-1PACK		C37(candle lamp) -E14 E12 RGBCW 4W	\$6.00	\$5.56	\$5.12
27	Zigbee wired gateway	TYHUB002		Input: USB 5V / 1A WIFI frequency: WiFi 2.4GHz Wireless protocol: Zigbee 3.0 Transmission distance: 10 ~ 30 meters Material: PC + ABS Product size: 95 * 95 * 23mm	\$28.00	\$26.00	\$25.00
28	Zigbee wireless gateway	TYHUB003		Input: USB 5V / 1A WIFI frequency: WiFi 2.4GHz Wireless protocol: Zigbee 3.0 Transmission distance: 10 ~ 30 meters Material: PC + ABS Product size: 95 * 95 * 23mm	\$15.60	\$15.60	\$15.60
29	Thermostat-wifi	HY312-WIFI		1. Power: 90-240Vac 50/60HZ 2. Range of temperature display: 0~70°C 3. Display accuracy: 0.5°C 4. Insulating condition: Normal environment 5. Probe sensor: NTC(10k)1% 6. Running program: Set per 1 week as a cycle 7. Contact capacity: 3A/250V(WW);16A/250V(WE) 8. Output: Switch relay 9. Working environment temperature: 0~90°C 10. Installation: Wall mounted or on battery seat 11. Range of temperature adjustment: 5~35°C 12. Size(mm): 86*86*30 Electrical Heating-16A Gas Boiler Heating-3A- Dry Contact	\$40.00	\$38.00	\$37.00

30	Thermostat-wifi	HYO8AC-2-WIFI-tuva-lexa-google-assitant-white/black		1. Power Supply: 220V 50/60Hz/ 2. Rated current: 3A/ 3. Set Point Range: 5-35/ 4. Ambient: 0-50 °C/ 5. Size: 86*86*14/ 6. Ambient temperature: 0°C-50°C/ 7. Installation: Flush Installation/ 8. Sensor ntc/ 9. Accuracy ±0.5°C/ 10. Protection Class IP30/11. Housing: PC+ABS pLstic/12 Storage temperature: 10 °C~60 °C 4-pipe; 2-pipe (choose from advanced option)	\$32.00	\$30.00	\$29.00
31	Smart home host	F6-6 inch		Color: Grey Overall dimension: 208*86*11.5mm Digging size: 175*75*50MM Touch Screen: 6 inch Display screen: 1440*720(IPS full view) CPU: Quad core Cortex 1.5G	\$145.00	\$140.00	\$130.00
32	Smart home host	F8-8 inch		Color: Grey Overall dimension: 214.6*114.6*11.5mm Digging size: 175*75*50MM Touch Screen: 7 inch Display screen: 1280*800(IPS full view) CPU: Quad core Cortex 1.5G ROM: 8G Horn power: 2* (10-25W) / 4* (10-25W) (MAX) Power input: ACC110-250V	\$230.00	\$220.00	\$210.00
33	Speaker	WYX1S1		5.25" speaker, each background music needs 4 speaker	\$22.15	\$22.15	\$21.15
34	Outdoor camera			IP67 waterproof Support: 64GB Storage MAX Night Vision Support 2 Way Audio Support Extend-Mic	\$26.27	\$26.27	\$26.27
35	Dome Camera	ZX-C43		Main Processor: XM530 image sensor: F37 High Definition: 1080P Video Compression: Smart H.264+ Rotation angle: Horizontal: 355° ; vertical: 90° Object tracking: Support Two-way Speech: Support Network Interface: 1*RJ45 , 10/100M10-100 Base-T, self-adaptable Ethernet port WIFI: 802.11b/g/n IP67 waterproof	\$28.22	\$26.87	\$25.00
36	curtain system	WCG1W1		below 2.16M	\$52.38	\$49.25	\$47.83
37		WCG1W2		2.16M--3.16M	\$57.14	\$53.73	\$52.17
38		WCG1W3		3.16M--4.16M	\$61.90	\$58.21	\$56.52
39		WCG1W4		4.16M--5.16M	\$69.84	\$65.67	\$63.77
40		WCG1W5		5.16M--6.16M	\$74.60	\$70.15	\$68.12
41		WCG1W6		6.16M--7.16M	\$82.54	\$77.61	\$75.36
42		WCG1W7		7.16M--8.16M	\$87.30	\$82.10	\$79.71

43	Roller curtain system	WDJ2T2		Loading:45kgs power:85w running	\$54.93	\$53.33	\$52.57
44		WCG3X3		roller channel,1meter price	\$12.10	\$11.74	\$11.57
45	Motion sensor	HW500A		Input Voltage: DC3V LR03; Low Power Undervoltage: $\leq 2.6V$; Detection Distance:10m; Working Temperature: $-10^{\circ}C \sim 50^{\circ}C$; Working Humidity: $\leq 95\%RH$; Wireless protocol: Zigbee 3.0	\$8.17	\$7.59	\$7.00
46	Door Sensor	MC500A		Input Voltage: DC3V LR03; Low Voltage Undervoltage: $\leq 2.6V$; Magnetic Control Distance: $\geq 20mm$; Work Temperature: $-10^{\circ}C \sim 50^{\circ}C$; Working Humidity: $\max \leq 95\%RH$; Wireless protocol: Zigbee 3.0	\$6.77	\$6.29	\$5.80
47	Temperature Humidity Sensor	WSD500A		●Operating voltage: 3V ●Battery type: 2 LR03AAA dry batteries (600mA) ●Static current: $\angle 10uA$ ●Alarm current: $\leq 15mA$ ●Low voltage and undervoltage: $\leq 2.2V$ ●zigbee3.0 ●Detection temperature: $-10^{\circ}C \sim 55^{\circ}C$ ●Detected humidity: 0-99%RH	\$7.47	\$6.94	\$6.40
48	Leaking sensor	SQ500B		●Operating voltage: 3V ●Battery type model: CR123A ●Static current: $\angle 10uA$ ●Alarm current: $\leq 15mA$ ●Low voltage and undervoltage: $\leq 2.6V$ ●Communication protocol: zigbee3.0 ●Working environment: $-10^{\circ}C \sim +50^{\circ}C$ ●Working humidity: maximum 95%RH	\$8.64	\$8.02	\$7.40
49	Smoke sensor	YG500A		●Operating voltage: 3V ●Battery type model: CR123A ●Static current: $\angle 10uA$ ●Alarm current: $\leq 15mA$ ●Low voltage and undervoltage: $\leq 2.6V$ ●Communication protocol: zigbee3.0 ●Working environment: $-10^{\circ}C \sim +50^{\circ}C$ ●Working humidity: maximum 95%RH	\$12.14	\$11.27	\$10.40
50	Gas sensor	RQ500A		●Input voltage: 85V-250V ●Alarm sound pressure: 70db/1m ●Alarm concentration: $6\%LEL \pm 3\%LEL$ ●WIFI: 802.11b/g/n ●Detection range: 20m³ ●Communication protocol: zigbee3.0 ●Installation method: ceiling installation ●Working temperature: $-10-50^{\circ}C$	\$12.84	\$11.92	\$11.00
51	Water valve	FM500A		Power supply voltage: 12V/1A Communication technology: Zigbee 3.0 Frequency of communication:2.4G Wireless Distance:30m(Open space) Valve pressure:1.6 Mpa Valve specifications:4, 6, 1 inch, 1.25 inch Close&Open valve time:5-10 seconds Torque:30-60 kgf.cm	\$16.80	\$15.60	\$14.40
52	Siren	JH300B		Using 8-bit micro-signal processor Wireless transmission of data signals Adopt STM process, strong anti-interference ability Battery: 3.7V polymer battery Standby current: $\leq 35uA$ Alarm current: $\leq 35mA$ Transmission distance: $\leq 200m$ (open distance) Installation method: wall hanging Ambient temperature: $-10^{\circ}C \sim 50^{\circ}C$	\$16.91	\$15.65	\$14.40

53	Smart door lock	X10		5050 double tongue lock body/60# single tongue, can be matched with 72 Series, 85 series and other lock bodies (special lock body prices need to be added Price), suitable for door locks with 38-45 door thickness Unlocking method: fingerprint/password/key/swipe card/wifi	\$45.00	\$40.00	\$35.00
54	Smart door lock	TQ-D1		1. Shell material: aluminum alloy 2. Panel material: all-metal material, surface IML parts imported material, fire-resistant materials, chemical fiber coating process 3. Unlocking method: face, fingerprint, card swiping, password, mechanical key, Tuya APP, temporary password 4. User data: 100 faces (50), fingerprints, passwords, and cards each 5. Power supply mode: large-capacity lithium battery 4200mAh	\$110.00	\$105.00	\$100.00