

Model	Rated voltage (AC V)	Rated current (AC A)	Rated capacity (kVa)	Cooling way
SPC3 -0025A	380	25	16	air cooling
SPC3 -0050A		50	33	
SPC3 -0075A		75	49	
SPC3 -0100A		100	66	
SPC3 -0150A		150	99	
SPC3 -0200A		200	132	
SPC3 -0250A		250	165	
SPC3 -0350A		350	230	
SPC3 -0450A		450	296	
Input		Main circuit voltage		
	Control power supply		AC220V±15%, 45~65HZ	
	Fan power supply		AC220V±15%, 45~65HZ	
Output	Output voltage		0 to 95% of the input voltage (phase-shifting control)	
	Output current		See "Product series"	
	Control mode		Open-loop, constant voltage, constant current, constant power, power regulation (zero-crossing) and LZ control	
	Load feature		Resistance, primary side of the transformer	
Main control features	Control signal		Analog and digital determined	
	Parameter setting		Keyboard setting	
	Analogue value input		5-channel programmable input (2-channel linear Opto-coupler Isolation, 3-channel non-isolation)	
	Switch value input		1-channel fixed, 4-channel programmable input	
	Relay output		3-channel programmable output	
	Analogue output		4-channel programmable output	
	Fan control		Automatically start/time-delay and stop fan cooling device	