

4G LTE Mobile WIFI (MIFI)

Model: L411A



- ✓ LTE Cat4 ASR1803S/L Cost effective Solution
- ✓ eSIM/VSIM support optional



SoC	ASR1803S CAT4 / ASR5803W	
Dimension	98*66*15mm	
Bands	LTE FDD B1/3/5/7/8/20/28AB, TDD B38/39/40/41, WCDMA 900/2100MHz (Bands support to be customized)	
Form factor	MIFI	
Battery	Li-ion Battery 2100mAh Working time: 5-6 hrs, Standby time: around 300 hrs (Depend on network)	
Wi-Fi	802.11 b/g/n, WIFI speed up to 72Mbps, max 10 users connection	
Memory	256Mb RAM	
Data Rates	LTE CAT4 FDD-LTE 150Mbps DL /50Mbps UL	
Hardware	USB	USB2.0, Type C
	SIM	3FF (eSIM / VSIM optional)
	LED	Battery/WIFI/Signal
	Antenna	Build-in FPC type
	Power Voltage	USB DC 5V
Software	Button	Reset(Pinhole), Power
	Update	FOTA & Local update
	Support OS	Compatible with Windows / MACOS / Linux / Android
	Others	IPv4/IPv6, SMS, Phonebook, SIM Lock, Firewall, Data statistics, WIFI Security
Operation Temperature	Operation Temperature: -10 to 55°C / Operation Humidity: 10% to 80%	
	Storage Temperature: -40 to 85°C / Storage Humidity: 5% to 95%	