



HiTi CS-310 Card Printer

►Main Functions and Features



ID card, Multi-functional Printing Performance

Single side Printing, edge-to-edge

Automatic Temperature and Humidity Detection

Experiencing the Super High Performance

Excellent Expansion Capability

Best Match with the Premium Software

Customer can change TPH once for free in the first year!!



►Technical specifications

Print Method	Single side Printing
Print Speed	Premium photo mode : 32 sec.(per YMCKO) Standard mode(Default): 25 sec. (per YMCKO)
Resolution	300dpi x 300dpi,256 levels per color
Dimensions & Weight	275mm(W)/508mm(L)/251mm(H); 9.1kg
Display	LCD screen(Multi-language),LED
Memory	32MB,1MB Flash
Software driver	Windows 2000/XP/2003; Mac driver
Communication Interface	USB 1.1/USB 2.0 full speed
Print Area	CR-80 86mm(L) x 54mm(W)
Accepted card Specification	0.3mm/0.5mm/0.8mm/1mm
Input hopper card capacity	100 cards(0.76mm/30mil thickness)
Output hopper card capacity	100 cards(0.76mm/30mil thickness)
Ribbon Options	YMCKO(200 prints) ,Resin K(1,000 prints)
Supply Voltage	110~240VAC
Supply Frequency	50HZ~60HZ
Operating Temperature	15° to 32℃/59℃to 89.6° F
Operating Humidity	20~75% non-condensing
Encoding Options	● Mag card encoder 300 Oe~4000 Oe Tracks 1,2,and 3 ● Contact IC encoder(embedded) ● Contactless IC encoder(Mifare type A;other types upon request)
Lamination model	Could be upgraded on site()
Cleaning tool	HiTi Card Printer PAVO clean kit