

## Mobile Payment Box HS-2001B

### Feature

- Quickly identify the screen 1D/2D code
- Very large reading window
- No plugins, lightning billing
- Body and data line integration design
- Non-slip drop design
- Compatible with a variety of systems

### Specification

|                         |                                                                                                                                                                                                                                                                                              |
|-------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Performance             |                                                                                                                                                                                                                                                                                              |
| Image Sensor            | 640×480 CMOS                                                                                                                                                                                                                                                                                 |
| Ambient light intensity | 0~100000Lux                                                                                                                                                                                                                                                                                  |
| Symbolize               | 1D: Code 128,UCC/EAN-128,AIM 128,EAN-8,EAN-13, ISSN, ISBN,UPC-E,UPC-A,Interleaved 2 of 5,ITF-6,ITF-14,Matrix 2 of 5(European Matrix 2 of 5),Industrial 25,Standard 25,Code 39,Codabar,Code 93,Code 11,Plessey,MSI-Plessey,RSS-14,RSS-Limited,RSS-Expand<br>2D:PDF417,Data Matrix,QR,Micro QR |
| Resolution              | ≥5mil                                                                                                                                                                                                                                                                                        |
| Typical Depth of Field  | QR CODE( 30MIL) 0-15CM<br>CODE 128 (10MIL) 0-12CM                                                                                                                                                                                                                                            |
| Scan Angle              |                                                                                                                                                                                                                                                                                              |
| Pitch                   | ±60°@ 0°Roll and 0° Skew                                                                                                                                                                                                                                                                     |
| Roll                    | 360°@ 0°Pitch and 0° Skew                                                                                                                                                                                                                                                                    |
| Skew                    | ±55°@ 0°Roll and 0° Pitch                                                                                                                                                                                                                                                                    |
| Symbol Contrast         | ≥30%                                                                                                                                                                                                                                                                                         |
| Interface               | RS-232, USB                                                                                                                                                                                                                                                                                  |
| Physical                |                                                                                                                                                                                                                                                                                              |
| Dimensions              | 102*82*73 mm(L*W*H)                                                                                                                                                                                                                                                                          |
| Weight                  | USB:228g<br>RS232:261g                                                                                                                                                                                                                                                                       |
| Notification            | Beep,LED indicator                                                                                                                                                                                                                                                                           |
| Current                 |                                                                                                                                                                                                                                                                                              |
| Maximum                 | <200mA                                                                                                                                                                                                                                                                                       |
| Operating               | 150mA±15mA                                                                                                                                                                                                                                                                                   |
| Standby                 | 80mA±2mA                                                                                                                                                                                                                                                                                     |
| Environmental           |                                                                                                                                                                                                                                                                                              |

Shenzhen HCC Technology Co., Ltd.

|                       |                        |
|-----------------------|------------------------|
| Operating Temperature | -20℃~50℃               |
| Storage Temperature   | -40℃~70℃               |
| Humidity              | 5%~95%(non-condensing) |

## Picture

