

Product Name	Melamine Laminated MDF		
Size	1220x2440mm		
Thickness	1.8~21mm		
Thickness Tolerance	+/-0.2mm (thickness<6mm), +/-0.3mm (thickness≥6mm)		
Face/Back	Wood veneer laminated first, then one side or double sides impregnated paper laminated		
Surface Treatment	Matt, texture, pitting or glossy		
Paper Color	Solid color (such as white, red, blue, orange, green, etc.) . Wood grain color(such as beech, cherry, walnut, oak, maple, sapeli, etc.). Fancy design color(marble, metal, linen, ire drawing). More than 300 kinds color are available.		
Material	Poplar, hardwood, and pine		
Glue	E0, E1, E2		
Grade	A grade or as clients requirement		
Density	560~800kg/m3		
Usage & Performance	Melamine laminated plywood is widely used for furniture, cabinet and interior decoration. With good properties, such as easy fabricability, water resistant, heat resistant, anti-static, easy cleaning, long-lasting and no seasonal effect.		
Packing	Standard Export	Inner Packing	Plywood is wrapped with plastic bag
	Pallet Packing	Outer Packing	Pallet is covered with plywood or carton and then steel tapes for strength
Loading Quantity	20’GP	8pallets/21cbm	
	40’GP	16pallets/48cbm	
	40’HQ	18pallets/52cbm	
MOQ	1x20’FCL		
Supply Ability	5000cbm/month		
Payment Terms	1) 30% TT in advance, 70% TT at sight of B/L copy. 2) 30% TT in advance, 70% L/C at sight. 3) 100% L/C at sight.		
Delivery Time	Within 15 days after receiving deposit or original L/C at sight.		