



L Lab Corporation



1

5th GaNPro 100W/102W GaN Charger
WORLD'S Highest Power Density

Expert in Switching Power



L Lab Corporation


100W/102W Ultra-Compact GaN Charger

102W 2C1A 超小型氮化镓充电器




单口使用

100W




Type-C1

100W



Type-C2

18W



USB


双口同充

65W+30W



Type-C1+Type-C2

65W+18W



Type-C1+USB


5V,3A



Type-C2+USB

三口同充

87W+5V, 3A(C2+A: 3Amax)



Type-C1+(Type-C2+USB)

Expert in Switching Power



L Lab Corporation



GaN2GO 102 Pro

50% Smaller, 102W Multiports GaNPro Charger




Innovation Integrated ONE-STOP housing design to avoid the risk of AC plug broken apart from upper case.

**Compatible with Lockable Multi-Country
AC Plug Adapters**

Expert in Switching Power



L Lab Corporation



GaN Chargers, 100W/102W Triple Ports USB-C Laptop AC Charger

Power Delivery 3.0, Compatible with 45W Samsung Fast charging

Built-in PFC circuit, 100W for any of USB C port

CEC/DOE VI compliance, standby power <0.3W

Foldable AC plug, easy for storage

Part#: PST-102C3-LB

Input: AC100-240V, 50/60Hz

If Single USB C is connected: (Supporting 5-11V/45W PPS)

USB C1 /C2 output: 任一USB C 口均为盲插100W 快充

DC 5/9/12/15V,3.0A, DC20V,5.0A(100W)

If Dual Ports are connected: (Supporting PPS)

--USB C1 Output: DC 5/9/12/15V,3.0A, DC20V,3.25A(65W)

USB C2 Output: DC 5/9V,3.0A/12V,2.5A(30W)

--USB C1 Output: DC 5/9/12/15V,3.0A, DC20V,3.25A(65W)

USB C3 Output(QC3.0): DC5V, 3.0A/9V, 2.0A/12V,1.5A(18W)

--USB-C2 + USB C3 Output: DC 5V,3.0A(15W)

If Triple ports are connected: (Supporting PPS)

USB C1 Output: DC 5/9/12/15V,3.0A, DC20.2V,4.30A(87W)

USB-C2 + USB C3 Output: DC 5V,3.0A(15W)


Dimension : 62x57x33 mm (2.44x2.24x1.30 inch)



Expert in Switching Power



L Lab Corporation



GaN Chargers, 100W/102W Triple Ports USB-C Laptop AC Charger

Power Delivery 3.0, Compatible with 45W Samsung Fast charging

Built-in PFC circuit, 100W for any of USB C port

CEC/DOE VI compliance, standby power <0.3W

Foldable AC plug, easy for storage

Part#: PST-102UC2-LB

Input: AC100-240V, 50/60Hz

If Single USB C is connected: (Supporting 5-11V/45W PPS)

USB C1 /C2 output: 任一USB C 口均为盲插100W 快充

DC 5/9/12/15V,3.0A, DC20V,5.0A(100W)

If Dual Ports are connected: (Supporting PPS)

--USB C1 Output: DC 5/9/12/15V,3.0A, DC20V,3.25A(65W)

USB C2 Output: DC 5/9V,3.0A/12V,2.5A(30W)

--USB C1 Output: DC 5/9/12/15V,3.0A, DC20V,3.25A(65W)

USB A Output(QC3.0): DC5V, 3.0A/9V, 2.0A/12V,1.5A(18W)

--USB-C2 + USB A Output: DC 5V,3.0A(15W)

If Triple ports are connected: (Supporting PPS)

USB C1 Output: DC 5/9/12/15V,3.0A, DC20.2V,4.30A(87W)

USB-C2 + USB A Output: DC 5V,3.0A(15W)


Dimension : 62x57x33 mm (2.44x2.24x1.30 inch)



Expert in Switching Power



L Lab Corporation



GaN Chargers, 100W/102W Triple Ports USB-C Laptop AC Charger

Power Delivery 3.0, Compatible with 45W Samsung Fast charging

Built-in PFC circuit, 100W for any of USB C port

CEC/DOE VI compliance, standby power <0.3W

Foldable AC plug, easy for storage

Part#: PST-100C2-LB

Input: AC100-240V, 50/60Hz

If Single USB C is connected: (Supporting 5-11V/45W PPS)

USB C1 /C2 output: 任一USB C 口均为盲插100W 快充

DC 5/9/12/15V,3.0A, DC20V,5.0A(100W)

If Dual Ports are connected: (Supporting PPS)

--USB C1 Output: DC 5/9/12/15V,3.0A, DC20V,3.25A(65W)

USB C2 Output: DC 5/9V,3.0A/12V,2.5A(30W)


Dimension : 62x57x33 mm (2.44x2.24x1.30 inch)



Expert in Switching Power



L Lab Corporation



GaN Chargers, 100W/102W Triple Ports USB-C Laptop AC Charger

Power Delivery 3.0, Compatible with 45W Samsung Fast charging

Built-in PFC circuit, 100W for any of USB C port

CEC/DOE VI compliance, standby power <0.3W

Foldable AC plug, easy for storage

Part#: PST-100C-LB

Input: AC100-240V, 50/60Hz

USB C output: (Supporting 5-11V/45W PPS)

DC 5/9/12/15V,3.0A, DC20V,5.0A(100W)


Dimension : 62x57x33 mm (2.44x2.24x1.30 inch)



Expert in Switching Power



L Lab Corporation



GaN Chargers, 100W/102W Triple Ports USB-C Laptop AC Charger

Power Delivery 3.0, Compatible with 45W Samsung Fast charging

Built-in PFC circuit, 100W for any of USB C port

CEC/DOE VI compliance, standby power <0.3W

Foldable AC plug, easy for storage

Part#: PST-100C-LB-CAB

Input: AC100-240V, 50/60Hz

USB C output: (Supporting 5-11V/45W PPS)

DC 5/9/12/15V, 3.0A, DC20V, 5.0A (100W)

Fixed Output cable: USB C 2.0, 1.5m (5ft)

Dimension: 62x57x33 mm (2.44x2.24x1.30 inch)



Expert in Switching Power