

产品名称	产品型号	产品参数	图片	认证
XR-STDE2A2C20	20W	AC OUTPUT:10A, 250V, 2500W DC OUTPUT:USB-C1/C2 + USB-A1/A2 C1/C2:PDO 5V=3.0A, 9V=2.22A, 12V=1.67A, 20W USB-A1/A2:QC 5V=3.0A, 9V=2.0A, 12V=1.5A, 18W C1+C2+A1+A2 Total:5V=3A 2X0.75 mm ² , extended core 1m		CE, LVD ERP, ROHS 主控硅动力SP9682NBB +慧能泰协议HUSB382A
XR-STDE2A2C30	30W	AC OUTPUT:10A, 250V, 2500W DC OUTPUT:USB-C1/C2 + USB-A1/A2 C1/C2:PDO 5V=3.0A, 9V=3A, 12V=2.5A, 15V=2.0A, 20V=1.5A, 30W USB-A1/A2:QC 27W MAX C1+C2+A1+A2 Total:5V=3A 2X0.75 mm ² , extended core 1m		CE, LVD ERP, ROHS 主控硅动力SP9684NBB +慧能泰协议HUSB382A
QR-RPDE2A2C20	20W 2A2C	C OUTPUT:16A, 250V, 4000W DC OUTPUT:USB-C1/C2 + USB-A1/A2 C1/C2:PDO 5V=3.0A, 9V=2.22A, 12V=1.67A, 20W USB-A1/A2:QC 5V=3.0A, 9V=2.0A, 12V=1.5A, 18W C1+C2+A1+A2 Total:5V=3A 3 X 1.5mm ² , AC线, 欧规, 长度1.5米		CB, CE, ROHS, REACH, ERP -TUV莱德 CNAS, SASO偏差, ISS145 偏差-LCS立讯
QR-RPDE2A2C30	30W 2A2C	AC OUTPUT:16A, 250V, 4000W DC OUTPUT:USB-C1/C2 + USB-A1/A2 C1/C2:PDO 5V=3.0A, 9V=3A, 12V=2.5A, 15V=2.0A, 20V=1.5A, 30W PPS:3.3V-11V=3A; 3.3V-16V/2A USB-A1/A2:QC 27W MAX C1+C2+A1+A2 Total:5V=3A 3 X 1.5mm ² , AC线, 欧规, 长度1.5米		CB, CE, ROHS, REACH, ERP
QR-RPDE2A2C45	45W 2A2C	AC OUTPUT:16A, 250V, 4000W DC OUTPUT:USB- C1/5V=3.0A, 9V=3.0A, 12V=3.0A, 15V=3.0A, 20V=2.25A, 45W USB-C2/:5V=3.0A USB-A1/:5V=3.0A USB-A2/:5V=3.0A USB-C1+USB-C2+USB-A1+USB-A2:30W+15W 3 X 1.5mm ² , AC线, 欧规, 长度1.5米		CB, CE, ROHS, REACH, ERP
XR-SPDE2A4C20 4C2A	20W4C2A 20W	AC OUTPUT:10A, 250V, 2500W DC OUTPUT:USB-C1/C2/C3/C4+USB-A1/A2 C1/C2/C3/C4:PDO 5V=3.0A, 9V=2.22A, 12V=1.67A, 20W USB-A1/A2:QC 5V=3.0A, 9V=2.0A, 12V=1.5A, 18W C1+C2+C3+C4+A1+A2 Total:5V=3A 3X1.5 mm ² , AC线, 欧规, 长度1.5米		CB, CE, ROHS, REACH, ERP
XR-SPDE2A4C30 4C2A	30W4C2A 30W	AC OUTPUT:10A, 250V, 2500W DC OUTPUT:USB-C1/C2/C3/C4+USB-A1/A2 PDO 5V=3.0A, 9V=3.0A, 12V=2.5A, 15V=2.0A, 20V=1.5A, 30W C1/C2/C3/C4:PDO 5V=3.0A, 9V=2.22A, 12V=1.67A, 9V=2.22A, 12V=1.67A, 20W USB-A1/A2:QC 5V=3.0A, 9V=2.0A, 12V=1.5A, 18W C1+C2+C3+C4+A1+A2 Total:5V=3A 3X1.5 mm ² , AC线, 欧规, 长度1.5米		CB, CE, ROHS, REACH, ERP

XR-SPDE2A4C45 4C2A	45W4C2A 45W	AC OUTPUT: 16A, 250V, 4000W DC OUTPUT: USB-C1/C2/C3/C4+USB-A1/A2 DC OUTPUT: USB-C1/5V=3.0A, 9V=3.0A, 12V=3.0A, 15V=3.0A, 20V=2.25A, 45W USB-C2/: 5V=3.0A USB-C3/: 5V=3.0A USB-C4/: 5V=3.0A USB-A1/: 5V=3.0A USB-A2/: 5V=3.0A USB-C1+USB-C2/USB-C3/USB-C4/USB-A1/USB-A2: 30W+15W 3 X 1.5mm ² , AC线, 欧规, 长度1.5米		CB, CE, ROHS, REACH, ERP
-----------------------	----------------	---	---	--------------------------