









R08403NS



SW R1 ED

360° rotation, ED
300° rotation, R1\SW



编码器规格书

ENCODERS SPECIFICATIONS

适用型号 : ED087、ED084 系列
 APPLICABLE MODELS: ED087、ED084 Series

一 构造 CONSTRUCTION

形状,寸法,依照图面规定

外观 各部应良好无锈蚀、裂痕、电镀不良现象

APPEARANCE: EVERY PART SHOULD BE FINISHED, NOT TO EXIST RUST

全回转角度 Total rotational angle,	360°
回转力矩 Rotational torque	2~24.5mN.m O~+70℃ 49.1mN.m Max. O~-20℃ (20~250gf.cm) (500gf.cm Max.)
轴押引强度 Push-pull strength	Push 5Kgf / Pull 3Kgf
定格电压 Voltage rating	DC 5V
定格电流 Current rating	1mA
最大使用电流 Maximum operating current	2.5mA
噪音 Chattering	10ms Max
接触抵抗 Contact resistance	10 Ω Max

出力信号 Out put signals	A Signal (A-COM) OFF ON B Signal (B-COM) OFF ON CW A Signal (A-COM) OFF ON B Signal (B-COM) OFF ON CCW Click position
-------------------------	--

分解能力 Resolution	10 Pulses
-----------------	-----------

定位数 Click point	20 Detents
--------------------	------------

定位点位置	A-COM: ON or OFF B-COM: Non provisions
-------	---

	$T_d = T/4 \pm T/6$
--	---------------------

位相差 Phase difference	A Signal (A-COM) OFF ON B Signal (B-COM) OFF ON Td Td Td T = Cycle
-------------------------	--

负荷比 Duty Ratio	50%±15% (18° ±5.4°)
----------------	---------------------

切换角度 Change-Over angle	18° ±3°
------------------------	---------

耐电压 Voltage proof	1 minute at 300V AC
-------------------	---------------------

绝缘抵抗 Insulation resistance	100M Ω min. at 250V DC
----------------------------	------------------------

使用环境温度 Usage environment temperature	-20℃~+70℃
--------------------------------------	-----------

耐焊接热 Bear to weld hot	260℃ 5S
-----------------------	---------

回转寿命 Rotational life	30,000 cycles
----------------------	---------------

东莞市长泰尔电子有限公司 DONG GUAN CHANG TAI ER ELECTRONICS CO.,LTD	制作 Approved	审核 Examine	核准 Approve