

Group Brands

Share
擎联®

泛想

学生云

ShareRDP
Shenzhen Share Technology Co., Ltd.

QINLAN

Cloud
Computer™

◆ Processor:

Model	FL120N
CPU	All winner A20 dual-core 1.2GHz

◆ Size& Color:

Size	150mm*80mm*28mm
Color/Material	Black/Plastic

◆ Parameter:

Memory	512MB
Flash	4GB
Power/power consumption	DC 5V 2A/10W
System	Linux
Server system	Windows XP/7/8.1/10, Windows 2003/2008 R2
resolution	800*600, 1024*768, 1366*768, 1280*1024, 1440*900, 1280*720, 1920*1080
I/O Ports	SPK*1, MIC*1, HDMI*1, DC*1, VGA*1, USB 2.0*4, LAN*1(100Mbps)
WIFI	Optional
Client side	RDP 8.1
VESA	Support

◆ Processor:

Model	FL700N
CPU	ARM cortex A17 4 cores 1.8Hz (RK3288)

◆ Size& Color:

Size	155mm*108mm*25mm
Color/Material	Black/Plastic、aluminium alloy

◆ Parameter:

Memory	1G
Flash	8G
Power/power consumption	DC 5V 3A/15W
System	Linux/Android
Server system	Windows XP/7/8.1/10, Windows 2003/2008 R2
resolution	800*600, 1024*768, 1280*720, 1366*768, 1440*900, 1440*900, 1600*900, 1920*1080
I/O Ports	SPK*1, MIC*1, HDMI*1, DC*1, VGA*1, USB 2.0*4, LAN*1(1000Mbps)
WIFI	Optional
Client side	RDP8.0/8.1/10.0-10.6, Citrix、vmware、spice/Android5.1/ubuntu1604 (One of the three forms)
VESA	Support

◆ Processor:

Model	FL800M
CPU	quad core, Cortex-A53 1.5GHz (RK3328)

◆ Size& Color:

Size	106mm*105mm*26mm
Color/Material	Black/Plastic

◆ Parameter:

Memory	512MB
Flash	4GB
Power/power consumption	DC 5V 2.5A/12W
System	ARM Architecture Linux system
Server system	win7/win8/win10/win2008/win2012 and so
resolution	800*600、1027*768、1280*720、1366*768、1440*900、1600*900、1920*1080
I/O Ports	SPK*1, MIC*1, HDMI*1, DC*1, VGA*1, USB 2.0*5, LAN*1(1000Mbps)
WIFI	Optional
Client side	RDP8.0/8.1/10.0-10.6
VESA	Support



◆ Processor:

Model	FL900N
CPU	ARM cortex A55 4 cores 2.0Hz (RK3568)

◆ Size& Color:

Size	154mm*104mm*30mm
Color/Material	Black/Aluminium alloy

◆ Parameter:

Memory	1GB
Flash	8GB
Power/power consumption	DC 5V 3A/15W
System	Linux/Android
Server system	Windows XP/7/8.1/10, Windows 2003/2008 R2
resolution	800*600, 1024*768, 1280*720, 1366*768, 1440*900, 1440*900, 1600*900, 1920*1080
I/O Ports	SPK*1, MIC*1, HDMI*1, DC*1, VGA*1, USB 2.0*5, USB 3.0*1 LAN*2(1000Mbps)
WIFI	Optional
Client side	RDP8.0/8.1/10.0-10.6、Citrix、vmware、 spice/ubuntu20.04/debian10/Android11
VESA	Support