

100W

- AC input parameters: AC 100-240V 50/60Hz 2.5A
- USB-C1 Output: 5V=3A, 9V=3A, 12V=3A, 15V=3A, 20V=5A (100W Max)
- USB-C2 Output: 5V=3A, 9V=3A, 12V=3A, 15V=3A, 20V=5A (100W Max)
- USB-A Output: 5V=3A, 9V=3A, 12V=2.5A (30W Max)
- USB-C1+USB-C2 output: 65W+30W (95W Max)
- USB-A+USB-C1 output: 30W+65W (95W Max)
- USB-A+USB-C2 output: 30W+65W (95W Max)
- USB-A+USB-C1+USB-C2 output: 18W+45W+30W (93W Max)
- Total output power: 100W Max
- USB-A (Support QC3.0)+USB-C (Support PD)
- Size: 45(L)90(W)X44.2(H)mm
- Color: White/Black

XJY-USB-72-100ACC (Smooth Surface)

XJY-USB-72K-100ACC (Pitted Surface)



140W

- AC input parameters: AC 100-240V 50/60Hz 3.5A
- USB-C1 Output: 5V=3A, 9V=3A, 12V=3A, 15V=3A, 20V=5A, 28V=5A (140W Max)
- USB-C2 Output: 5V=3A, 9V=3A, 12V=3A, 15V=3A, 20V=5A, 28V=5A (140W Max)
- USB-C1+USB-C2 output: 65W+65W (130W Max)
- Total output power: 140W Max
- No-load power: 0.3W Max
- USB-C (Support PD3.1+QC5.0)
- Size: 45(L)90(W)X44.2(H)mm
- Material: PC
- Color: White/Black

XJY-USB-72B-140CC (Smooth Surface)

XJY-USB-72BK-140CC (Pitted Surface)

