

# SHENZHEN DALL DISPLAYS CO., LTD

Professional manufacturer for terminal display

Tel:86 755 29514486 Fax:86 755 29514480

Linkman:Mr.Mark

Email:mark@dalled.com

www.dalled.com

21.5"/23.8" ALL IN ON PC

|                          |                                                                          |                                    |                                   |
|--------------------------|--------------------------------------------------------------------------|------------------------------------|-----------------------------------|
| Brand                    | OEM                                                                      | Series                             | A2000                             |
| Screen                   |                                                                          |                                    |                                   |
| Screen size              | 21.5 inch/23.8inch Optional                                              | Resolution                         | 1920*1080P                        |
| Aspect ratio             | 16:09.                                                                   | Display Type                       | LED                               |
| CPU                      |                                                                          |                                    |                                   |
| Brand                    | Intel Core I3 3rd Gen 2.4Ghz<br>I3/I5/I7,J1900 AMD A6/A8/A10<br>Optional | Frequency                          | 2.0GHz to 3.9GHz<br>Optional      |
| Hard disk                | SSD 128G/256G/512G,HHD<br>500GB/1TB /2TB Optional                        | Memory                             | 4G/8G/16G Optional                |
| Graphics                 | Intel HD Graphics4000                                                    | LAN                                | 1000Mbit LAN+wifi                 |
| integrated<br>Module     | WIFI 802.11B/G/N<br>Agreement,support 1000M                              | Optical Drive<br>Type              | CD-ROM/DVD-<br>ROM                |
| Audio                    |                                                                          |                                    |                                   |
| Camera<br>2.0M pixel     | Hi-Derinition Audio CODEC                                                | Stereo Speaker                     | High Quakity<br>Mic(support)      |
| I/O Interface            |                                                                          |                                    |                                   |
| Power port               | ×1                                                                       | HDMI                               | ×1                                |
| Earphone-in<br>jack      | ×1                                                                       | VGA/LAN                            | ×1                                |
| Microphone<br>-out jack  | ×1                                                                       | USB                                | ×4                                |
| Power Adaptor            |                                                                          |                                    |                                   |
| Input                    | 100-240V AC ,50/60Hz<br>Universal                                        | Output                             | 12V Direct Current<br>,6A,60W     |
| Accessories              |                                                                          |                                    |                                   |
| Power cable              | ×1                                                                       | Power adaptor                      | ×1                                |
| User'S<br>manual         | ×1                                                                       | Keyboard/Mouse                     | ×1                                |
| Material                 |                                                                          | Mg-Al alloy base,ABS plastic shell |                                   |
| Optional                 |                                                                          |                                    |                                   |
| support                  | External USB CD/DVD driver                                               | support                            | Compatible with<br>win7/8/10Linux |
| Environment              |                                                                          |                                    |                                   |
| Operating<br>Temperature | 0°C to 40°C                                                              | Storage<br>Temperature             | -20°Cto 60°C                      |