



Model: DXE231

23.1inch Shelf Edge LCD Display

Suitable for 600mm shelves



显示/LCD Spec	
尺寸/Size	23.1"LCD Panel
显示区域/Active area	585.6(H) ×48.19(V)mm
分辨率/Resolution	1920×158(RGB) 83PPI
亮度/Brightness	400cd/m ² (Typ.)
对比度/Contrast ratio	3000:1 (Typ.) (TM)
显示色彩/Display color	16.7M , 72% NTSC
背光源/Backlight	WLED
可视角度/Viewing angles	88/88/88/88 (Typ.)(CR≥10)
响应时间/Response time	9.5 (Typ.)(G to G) ms
液晶屏寿命/Lifespan	≥30000 hours
主板规格/Motherboard Spec	
芯片/CPU	Rockchip PX30 Quad core ARM Cortex-A35
内存/RAM	1G DDR3(1G/2G for optional可选)
内置存储/ROM	8G EMMC(8G/16G/32G/64GEMMC for optional可选)
外置存储/Memory extension	最大支持64G TF存储卡, TF Card extension with the highest support for 64GB
操作系统/System	Android 8.1
网络/Intenet	支持2.4G无线WIFI接入, Support 2.4G WIFI connection
定时时钟/RTC real time clock	支持定时开关机功能, Support timing on / off function
接口/Interfaces	1xTF card slot/ 1x micro-USB(OTG)/ 1*Type-c(DC 12v)
整机规格/Display Spec	
电压/Operating voltage	100-240V(50/60Hz)
功率/Power consumption	≤16W
外观尺寸/Outline Dimensions	597*60*15mm
安装方式/Installation	挂墙式（支持壁挂板安装和葫芦孔两种挂墙方式）; Mounting bracket
外壳材质/material	金属钣金结构设计; Sheet Metal materials
净重/Net	≤0.75KG
表面处理/Surface treatment	黑色金属烤漆, Black metal paint
环境/Environment	
存储环境 /Storage Environment	Temperature: -20℃~60℃ Humidity: 5%~95% Atmospheric Pressure: 86kPa~104kPa
工作环境 /Working Environment	Temperature: 0℃~50℃ Humidity: 10%~85% Atmospheric Pressure: 86KPa~104KPa
包装清单/Packing list	

显示器/Display	1pc
OTG数据线/Cable	1pc (OTG cable, micro USB to USB 2.0)
适配器/Adapeter	1pc (12V-2A)
壁挂支架/Bracket	1pc
认证/Certifications	
CE	YES (Issued by SGS)
RoHS	YES (Issued by SGS)
REACH	YES (Issued by SGS)
FCC ID	YES (Issued by SGS)
信息发布系统CMS Software (可选/Optional)	