

B&T ZHANGZHOU (CABLE) CO.,LTD

UL3302

Halogen Free Crosslinked Wire 无卤交联线

■ 产品说明:

- 额定温度: 105℃
- 额定电压: 30V
- 参考标准: UL758,UL1581
- 导体使用单支或绞合 40AWG 以上镀锡或裸铜
- FR-XLPE 绝缘, 符合 ROHS 环保标准
- 通过 UL 水平阻燃测试
- 使用标准绝缘厚度、易裁线、易剥皮
- 用于一般电子、电器设备内部连接线

■ PRODUCT DESCRIPTION

- Rated temperature: 105℃
- Rated voltage: 30V
- Reference standard: UL758,UL1581
- Solid or stranded ,tinned or bare copper conductor 40AWG min.
- FR-XLPE insulation, comply with ROHS environmental standard
- Passes UL Horizontal flame test
- Uniform insulation thickness to ensure easy stripping and cutting
- For general purpose internal wiring of appliance



■ 印字 MARKING

■ 产品结构 CABLE CONSTRUCTION

规格 AWG	导体 CONDUCTOR		绝缘 INSULATION		最大导体电阻 MAX.COND. RESISTANCE (Ω/km,20°C,DC)	耐压强度 DIELECTRIC STRENGTH (VAC, 1min)
	构造 CONSTRUCTION (No./mm)	外径 DIA. (mm)	厚度 THICKNESS (mm)	外径 O.D. (mm)		
36	7/0.05	0.15	0.15	0.45	1549	500
34	7/0.064	0.19	0.15	0.50	966	500
32	7/0.08	0.24	0.18	0.60	588.85	500
30	1/0.254	0.25	0.20	0.65	361	500
	7/0.10	0.30	0.20	0.70	381	
28	1/0.32	0.32	0.19	0.70	227	500
	7/0.127	0.38	0.21	0.80	239	
	7/0.127OS-1*	0.38	0.21	0.80	239	
26	1/0.404	0.40	0.25	0.90	143	500
	7/0.16	0.48	0.26	1.00	150	
	7/0.16 OS-1*	0.48	0.26	1.00	150	
24	1/0.511	0.51	0.24	1.00	89.3	500
	11/0.16	0.61	0.25	1.10	94.2	
	7/0.200S-1*	0.60	0.25	1.10	94.2	
22	1/0.643	0.64	0.25	1.15	56.4	500
	17/0.16	0.76	0.27	1.30	59.4	
	7/0.254 OS-1*	0.76	0.27	1.30	59.4	

备注. OS-1*: 先镀后绞再镀铜线.

Note. OS-1*:Over-coated tinned stranded copper